

	1	2	3	4	5	6	7																																																																														
A								A																																																																													
B								B																																																																													
C	Conductor: [26AWG(0.16/7)Bare Copper]x6C Insulation: [PP6331 ID:0.95±0.03]x6C Jacket: PVC NOUL 65P							C																																																																													
D								D																																																																													
E	<table border="1"> <thead> <tr> <th>P1</th> <th>P2</th> </tr> </thead> <tbody> <tr> <td>1 <u>WHITE</u></td> <td>1</td> </tr> <tr> <td>2 <u>BLACK</u></td> <td>2</td> </tr> <tr> <td>3 <u>RED</u></td> <td>3</td> </tr> <tr> <td>4 <u>GREEN</u></td> <td>4</td> </tr> <tr> <td>5 <u>YELLOW</u></td> <td>5</td> </tr> <tr> <td>6 <u>BLUE</u></td> <td>6</td> </tr> </tbody> </table>							P1	P2	1 <u>WHITE</u>	1	2 <u>BLACK</u>	2	3 <u>RED</u>	3	4 <u>GREEN</u>	4	5 <u>YELLOW</u>	5	6 <u>BLUE</u>	6	E																																																															
P1	P2																																																																																				
1 <u>WHITE</u>	1																																																																																				
2 <u>BLACK</u>	2																																																																																				
3 <u>RED</u>	3																																																																																				
4 <u>GREEN</u>	4																																																																																				
5 <u>YELLOW</u>	5																																																																																				
6 <u>BLUE</u>	6																																																																																				
F								F																																																																													
G	<table border="1"> <thead> <tr> <th>Part Number</th> <th>Drawing Number</th> <th>Wire Length "L"</th> <th>Jacket Color</th> <th>Cut Length</th> </tr> </thead> <tbody> <tr> <td>AT-S-26-6/6/S-5/R-R</td> <td>A</td> <td>1,525±20(5ft)</td> <td>Silver</td> <td>1,525-1,535mm</td> </tr> <tr> <td>AT-S-26-6/6/S-7/R-R</td> <td>B</td> <td>2,135±30(7ft)</td> <td>Silver</td> <td>2,135-2,145mm</td> </tr> <tr> <td>AT-S-26-6/6/S-10/R-R</td> <td>C</td> <td>3,050±60(10ft)</td> <td>Silver</td> <td>3,050-3,060mm</td> </tr> <tr> <td>AT-S-26-6/6/S-12/R-R</td> <td>D</td> <td>3,660±60(12ft)</td> <td>Silver</td> <td>3,660-3,670mm</td> </tr> <tr> <td>AT-S-26-6/6/S-14/R-R</td> <td>E</td> <td>4,270±60(14ft)</td> <td>Silver</td> <td>4,270-4,280mm</td> </tr> <tr> <td>AT-S-26-6/6/S-25/R-R</td> <td>F</td> <td>7,625±100(25ft)</td> <td>Silver</td> <td>7,625-7,635mm</td> </tr> <tr> <td>AT-S-26-6/6/S-50/R-R</td> <td>G</td> <td>15,250±150(50ft)</td> <td>Silver</td> <td>15,250-15,260mm</td> </tr> </tbody> </table>							Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-6/6/S-5/R-R	A	1,525±20(5ft)	Silver	1,525-1,535mm	AT-S-26-6/6/S-7/R-R	B	2,135±30(7ft)	Silver	2,135-2,145mm	AT-S-26-6/6/S-10/R-R	C	3,050±60(10ft)	Silver	3,050-3,060mm	AT-S-26-6/6/S-12/R-R	D	3,660±60(12ft)	Silver	3,660-3,670mm	AT-S-26-6/6/S-14/R-R	E	4,270±60(14ft)	Silver	4,270-4,280mm	AT-S-26-6/6/S-25/R-R	F	7,625±100(25ft)	Silver	7,625-7,635mm	AT-S-26-6/6/S-50/R-R	G	15,250±150(50ft)	Silver	15,250-15,260mm	G																																					
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																																																																	
AT-S-26-6/6/S-5/R-R	A	1,525±20(5ft)	Silver	1,525-1,535mm																																																																																	
AT-S-26-6/6/S-7/R-R	B	2,135±30(7ft)	Silver	2,135-2,145mm																																																																																	
AT-S-26-6/6/S-10/R-R	C	3,050±60(10ft)	Silver	3,050-3,060mm																																																																																	
AT-S-26-6/6/S-12/R-R	D	3,660±60(12ft)	Silver	3,660-3,670mm																																																																																	
AT-S-26-6/6/S-14/R-R	E	4,270±60(14ft)	Silver	4,270-4,280mm																																																																																	
AT-S-26-6/6/S-25/R-R	F	7,625±100(25ft)	Silver	7,625-7,635mm																																																																																	
AT-S-26-6/6/S-50/R-R	G	15,250±150(50ft)	Silver	15,250-15,260mm																																																																																	
H	Unit: mm RoHS Compliant <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th colspan="3"></th> <th>Date</th> <th>Name</th> <th colspan="2">Title</th> </tr> </thead> <tbody> <tr> <td colspan="2">TOLERANCE</td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>26.06.13</td> <td>Wilson</td> <td>Modular cable - Straight/Reversed 6P6C 50µ", 26AWG, Silver, 5-50 feet</td> </tr> <tr> <td>X.</td> <td>±X</td> <td></td> <td></td> <td></td> <td>Approved</td> <td>26.06.13</td> <td>Groll</td> <td>ASSMANN WSW-No.</td> </tr> <tr> <td>X.X</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AT-S-26-6/6/S-xx/R-R</td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawing-No.</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td colspan="3" rowspan="3"> ASSMANN WSW components </td> <td>rev00</td> </tr> <tr> <td>X.°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td>Replace</td> <td>Sheet</td> </tr> <tr> <td>X.X°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td>1/1</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="3"></td> </tr> </tbody> </table>							Scale	Free				Date	Name	Title		TOLERANCE					Drawn	26.06.13	Wilson	Modular cable - Straight/Reversed 6P6C 50µ", 26AWG, Silver, 5-50 feet	X.	±X				Approved	26.06.13	Groll	ASSMANN WSW-No.	X.X	±X							AT-S-26-6/6/S-xx/R-R	X.XX	±X							Drawing-No.	DIM	TOL				ASSMANN WSW components			rev00	X.°	±X°				Replace	Sheet	X.X°	±X°					1/1	Angle	TOL	Id.	Modification	Date	Name				H
Scale	Free				Date	Name	Title																																																																														
TOLERANCE					Drawn	26.06.13	Wilson	Modular cable - Straight/Reversed 6P6C 50µ", 26AWG, Silver, 5-50 feet																																																																													
X.	±X				Approved	26.06.13	Groll	ASSMANN WSW-No.																																																																													
X.X	±X							AT-S-26-6/6/S-xx/R-R																																																																													
X.XX	±X							Drawing-No.																																																																													
DIM	TOL				ASSMANN WSW components			rev00																																																																													
X.°	±X°							Replace	Sheet																																																																												
X.X°	±X°								1/1																																																																												
Angle	TOL	Id.	Modification	Date	Name																																																																																
	1	2	3	4	5	6	7																																																																														