

	1	2	3	4	5	6	7																																								
A								A																																							
B								B																																							
C								C																																							
D	Conductor: [26AWG(0.16/7)Bare Copper]x8C Insulation: [PP6331 ID:0.95±0.03]x8C Jacket: PVC NOUL 65P A, B, C, D E, F, G Note for plug: - Material: Housing-polycarbonate, clear. - Terminal-0.36[.014] thick phosphor bronze. - Thick gold in localized gold plate. - Area, Gold Flash over the remainder. - Over 2.54mm[.000100] thick nickel underplate. <table><thead><tr><th>Part Number</th><th>Drawing Number</th><th>Wire Length "L"</th><th>Jacket Color</th><th>Cut Length</th></tr></thead><tbody><tr><td>AT-S-26-8/8/S-5/R-R</td><td>A</td><td>1,525±20(5ft)</td><td>Silver</td><td>1,525-1,535mm</td></tr><tr><td>AT-S-26-8/8/S-7/R-R</td><td>B</td><td>2,135±30(7ft)</td><td>Silver</td><td>2,135-2,145mm</td></tr><tr><td>AT-S-26-8/8/S-10/R-R</td><td>C</td><td>3,050±60(10ft)</td><td>Silver</td><td>3,050-3,060mm</td></tr><tr><td>AT-S-26-8/8/S-12/R-R</td><td>D</td><td>3,660±60(12ft)</td><td>Silver</td><td>3,660-3,670mm</td></tr><tr><td>AT-S-26-8/8/S-14/R-R</td><td>E</td><td>4,270±60(14ft)</td><td>Silver</td><td>4,270-4,280mm</td></tr><tr><td>AT-S-26-8/8/S-25/R-R</td><td>F</td><td>7,625±100(25ft)</td><td>Silver</td><td>7,625-7,635mm</td></tr><tr><td>AT-S-26-8/8/S-50/R-R</td><td>G</td><td>15,250±150(50ft)</td><td>Silver</td><td>15,250-15,260mm</td></tr></tbody></table>							Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-8/8/S-5/R-R	A	1,525±20(5ft)	Silver	1,525-1,535mm	AT-S-26-8/8/S-7/R-R	B	2,135±30(7ft)	Silver	2,135-2,145mm	AT-S-26-8/8/S-10/R-R	C	3,050±60(10ft)	Silver	3,050-3,060mm	AT-S-26-8/8/S-12/R-R	D	3,660±60(12ft)	Silver	3,660-3,670mm	AT-S-26-8/8/S-14/R-R	E	4,270±60(14ft)	Silver	4,270-4,280mm	AT-S-26-8/8/S-25/R-R	F	7,625±100(25ft)	Silver	7,625-7,635mm	AT-S-26-8/8/S-50/R-R	G	15,250±150(50ft)	Silver	15,250-15,260mm
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																											
AT-S-26-8/8/S-5/R-R	A	1,525±20(5ft)	Silver	1,525-1,535mm																																											
AT-S-26-8/8/S-7/R-R	B	2,135±30(7ft)	Silver	2,135-2,145mm																																											
AT-S-26-8/8/S-10/R-R	C	3,050±60(10ft)	Silver	3,050-3,060mm																																											
AT-S-26-8/8/S-12/R-R	D	3,660±60(12ft)	Silver	3,660-3,670mm																																											
AT-S-26-8/8/S-14/R-R	E	4,270±60(14ft)	Silver	4,270-4,280mm																																											
AT-S-26-8/8/S-25/R-R	F	7,625±100(25ft)	Silver	7,625-7,635mm																																											
AT-S-26-8/8/S-50/R-R	G	15,250±150(50ft)	Silver	15,250-15,260mm																																											