

	1	2	3	4	5	6	7																																																																																											
A								A																																																																																										
B								B																																																																																										
C								C																																																																																										
D	<table><tr><td>P1</td><td>P2</td></tr><tr><td>1 WHITE</td><td>1</td></tr><tr><td>2 ORANGE</td><td>2</td></tr><tr><td>3 BLACK</td><td>3</td></tr><tr><td>4 RED</td><td>4</td></tr><tr><td>5 GREEN</td><td>5</td></tr><tr><td>6 YELLOW</td><td>6</td></tr><tr><td>7 BLUE</td><td>7</td></tr><tr><td>8 BROWN</td><td>8</td></tr></table>							P1	P2	1 WHITE	1	2 ORANGE	2	3 BLACK	3	4 RED	4	5 GREEN	5	6 YELLOW	6	7 BLUE	7	8 BROWN	8	D																																																																								
P1	P2																																																																																																	
1 WHITE	1																																																																																																	
2 ORANGE	2																																																																																																	
3 BLACK	3																																																																																																	
4 RED	4																																																																																																	
5 GREEN	5																																																																																																	
6 YELLOW	6																																																																																																	
7 BLUE	7																																																																																																	
8 BROWN	8																																																																																																	
E	Note for plug: - Material: Housing-polycarbonate, clear. - Terminal-0.36[.014] thick phosphor bronze. - Thick gold in localized gold plate. - Area, Gold Flash over the remainder. - Over 2.54mm[.000100] thick nickel underplate. <table><thead><tr><th>Part Number</th><th>Drawing Number</th><th>Wire Length "L"</th><th>Jacket Color</th><th>Cut Length</th></tr></thead><tbody><tr><td>AT-S-26-8/8/W-5/R-R</td><td>A</td><td>1,525±20(5ft)</td><td>White</td><td>1,525-1,535mm</td></tr><tr><td>AT-S-26-8/8/W-7/R-R</td><td>B</td><td>2,135±30(7ft)</td><td>White</td><td>2,135-2,145mm</td></tr><tr><td>AT-S-26-8/8/W-10/R-R</td><td>C</td><td>3,050±60(10ft)</td><td>White</td><td>3,050-3,060mm</td></tr><tr><td>AT-S-26-8/8/W-12/R-R</td><td>D</td><td>3,660±60(12ft)</td><td>White</td><td>3,660-3,670mm</td></tr><tr><td>AT-S-26-8/8/W-14/R-R</td><td>E</td><td>4,270±60(14ft)</td><td>White</td><td>4,270-4,280mm</td></tr><tr><td>AT-S-26-8/8/W-25/R-R</td><td>F</td><td>7,625±100(25ft)</td><td>White</td><td>7,625-7,635mm</td></tr><tr><td>AT-S-26-8/8/W-50/R-R</td><td>G</td><td>15,250±150(50ft)</td><td>White</td><td>15,250-15,260mm</td></tr></tbody></table>							Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-8/8/W-5/R-R	A	1,525±20(5ft)	White	1,525-1,535mm	AT-S-26-8/8/W-7/R-R	B	2,135±30(7ft)	White	2,135-2,145mm	AT-S-26-8/8/W-10/R-R	C	3,050±60(10ft)	White	3,050-3,060mm	AT-S-26-8/8/W-12/R-R	D	3,660±60(12ft)	White	3,660-3,670mm	AT-S-26-8/8/W-14/R-R	E	4,270±60(14ft)	White	4,270-4,280mm	AT-S-26-8/8/W-25/R-R	F	7,625±100(25ft)	White	7,625-7,635mm	AT-S-26-8/8/W-50/R-R	G	15,250±150(50ft)	White	15,250-15,260mm	E																																																		
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																																																																														
AT-S-26-8/8/W-5/R-R	A	1,525±20(5ft)	White	1,525-1,535mm																																																																																														
AT-S-26-8/8/W-7/R-R	B	2,135±30(7ft)	White	2,135-2,145mm																																																																																														
AT-S-26-8/8/W-10/R-R	C	3,050±60(10ft)	White	3,050-3,060mm																																																																																														
AT-S-26-8/8/W-12/R-R	D	3,660±60(12ft)	White	3,660-3,670mm																																																																																														
AT-S-26-8/8/W-14/R-R	E	4,270±60(14ft)	White	4,270-4,280mm																																																																																														
AT-S-26-8/8/W-25/R-R	F	7,625±100(25ft)	White	7,625-7,635mm																																																																																														
AT-S-26-8/8/W-50/R-R	G	15,250±150(50ft)	White	15,250-15,260mm																																																																																														
F	SEC: A=A							F																																																																																										
G	Unit: mm RoHS Compliant <table><thead><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th>Date</th><th>Name</th><th>Title</th></tr></thead><tbody><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>28.06.13</td><td>Wilson</td></tr><tr><td>X.</td><td>±X</td><td></td><td></td><td></td><td></td><td rowspan="2">Approved</td><td rowspan="2">28.06.13</td><td rowspan="2">Groll</td></tr><tr><td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td colspan="3" rowspan="3"> ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us </td></tr><tr><td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±X°</td><td></td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="3">Drawing-No.</td></tr><tr><td colspan="6"></td><td colspan="2">Replace</td><td>rev00</td></tr><tr><td colspan="6"></td><td colspan="2"></td><td>Sheet 1/1</td></tr></tbody></table>							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	28.06.13	Wilson	X.	±X					Approved	28.06.13	Groll	X.X	±X					X.XX	±X								DIM	TOL					ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us			X.°	±X°					X.X°	±X°					Angle	TOL	Id.	Modification	Date	Name	Drawing-No.									Replace		rev00									Sheet 1/1	G
Scale	Free					Date	Name	Title																																																																																										
TOLERANCE						Drawn	28.06.13	Wilson																																																																																										
X.	±X					Approved	28.06.13	Groll																																																																																										
X.X	±X																																																																																																	
X.XX	±X																																																																																																	
DIM	TOL					ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us																																																																																												
X.°	±X°																																																																																																	
X.X°	±X°																																																																																																	
Angle	TOL	Id.	Modification	Date	Name	Drawing-No.																																																																																												
						Replace		rev00																																																																																										
								Sheet 1/1																																																																																										
H	<table><tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td></tr></table>							1	2	3	4	5	6	7	H																																																																																			
1	2	3	4	5	6	7																																																																																												