



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B021-000-17

Rackmount Console - 1U Rackmount Console with 17" LCD



Highlights

- Control an entire network in just 1U of rack space; includes keyboard, 17" LCD screen, and touch pad
- Features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Connects to a PS/2 or USB server or KVM switch
- Supports video resolutions up to 1366 x 768
- Rackmountable in 19-inch system rack (1U), from 27" to 42" deep

Description

Tripp Lite's B021-000-17 1U Rackmount Console features an integrated 17" LCD panel, full 88-key keyboard, and touch pad, all in a 1U rackmountable housing. The included KVM cable kit allows for connection to a PS/2 computer or KVM, and a PS/2 to USB adapter is included, which can be used to connect to a USB computer or KVM. The unit features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.. Your peripheral device connects to the USB type A port on the front of the unit, and your computer connects to the USB type A port on the back of the unit using a Tripp Lite [UR020-Series](#) type A M/M cable. Constructed of heavy-duty steel housing.

Applications

- Use where rack space is at a premium, and where a Server/KVM display is needed.

System Requirements

- Computer or KVM with a VGA monitor port and USB or PS/2 keyboard/mouse ports

Package Includes

- 1- B021-000-17 1U Rackmount Console
- 1- KVM Cable Kit (HD15M to HD15M + 2 PS/2 Male)
- 1-PS/2 to USB Adapter
- 1- C13 to 5-15P Power Cord
- 1- User Manual

Features

- Space savings with 1U 19-inch, rack-mount drawer design
- Features 17-inch LCD TFT active-matrix, color panel
- Features a USB pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Supports resolutions of up to 1366 x 768
- Included PS/2 to USB adapter allows for connection to a USB computer or KVM
- Sleep mode when the monitor cover is closed
- Input 120/240 VAC
- Constructed of heavy-duty steel housing

Specifications

OVERVIEW

| | |
|-------------------------------------|--|
| PC/Server | VGA; USB; PS/2 |
| INPUT | |
| Electrical Consumption | (Line Mode) 30W / (Standby Mode) 5W |
| UPC ASSIGNMENT | |
| Unit Carton UPC# | 037332125279 |
| PHYSICAL | |
| Color | Black |
| Style | 1U Rack Console (non-KVM) |
| ENVIRONMENTAL | |
| BTUs | (Line Mode) 102 BTU/Hr / (Standby Mode) 17.06 BTU/Hr |
| CONNECTIONS | |
| Connector A |  HD15 (FEMALE) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

Related Items

Optional Products

| Related Model | Description | Qty. |
|------------------------------|---|------|
| B004-008 | KVM Switch - 8-Port 1U Rackmount KVM Switch | 1 |
| B019-000 | KVM Switch Accessories - 2-Post Rackmount Bracket for B020,B021, B040, and B070 Consoles and KVM Consoles | 1 |
| B022-U16 | KVM Switch - 16-Port NetDirector 1U Rackmount KVM Switch | 1 |
| UR020-003 | Reversible USB 2.0 A-Male to A-Male Cable - 3ft | 1 |
| UR020-006 | Universal Reversible USB 2.0 A-Male to A-Male Cable - 6ft | 1 |
| UR020-010 | Universal Reversible USB 2.0 A-Male to A-Male Cable - 10ft | 1 |
| B072-016-IP2 | 16-Port, 2+1 User NetCommander Cat5 IP KVM Switch | 1 |
| B072-016-IP4 | 16-Port, 4+1 User NetCommander Cat5 IP KVM Switch | 1 |
| WEXT-KVM-A1 | 1-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| WEXT-KVM-A2 | 2-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| WEXT-KVM-A3 | 3-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| WEXT-KVM-A4 | 4-Year Warranty Extension - For select KVM Switches (see specific models for eligibility) | 1 |
| B072-032-IP2 | 32-Port, 2+1 User NetCommander Cat5 IP KVM Switch | 1 |
| B072-032-IP4 | 32-Port, 4+1 User NetCommander Cat5 IP KVM Switch | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3150.

