


(2,54 mm) .100"

**BBS, BBL, BHS, BBD, BDL SERIES**

# MACHINED BOARD STACKING STRIPS

**Mates with:**  
SS, SD, HSS, SL, SDL,  
ESS, ESD

## FEATURES

- Low profile design achieves (3,89 mm) .153" board spacings when mated with SL Series.
- Choice of precision machined (BXX Series) or coined (LBS Series) terminals.
- Approach the reliability of a permanent connection with the flexibility of a separable connection.

## SPECIFICATIONS

For complete specifications see [www.samtec.com?BBS](http://www.samtec.com?BBS),  
[www.samtec.com?BBD](http://www.samtec.com?BBD),  
[www.samtec.com?BBL](http://www.samtec.com?BBL) or  
[www.samtec.com?BDL](http://www.samtec.com?BDL)

**BBS, BBD, BBL, BDL**



**Insulator Material:**  
Black Glass Filled Polyester  
(BBS, BBD, BBL)  
Black High Temp Nylon (BDL)

**Temperature Range:**  
-55°C to +125°C

**Terminal Material:**  
Phosphor Bronze or Brass

**Plating:**  
Au or Sn over 50µ" (1,27 µm) Ni

**Current Rating:**  
1A per contact

**RoHS Compliant:**  
Yes

**Lead-Free Solderable:**  
Yes

**Wave only**

## SPECIFICATIONS

For complete specifications see [www.samtec.com?BBS](http://www.samtec.com?BBS)

**BBS**

Same as BBS except:



**Insulator Material:**  
Black Liquid Crystal Polymer

**RoHS Compliant:**  
Yes

**Lead-Free Solderable:**  
Wave, or reflow with all Au

**Wave, or reflow with all Au**

**Note:** Some lengths, styles and options are non-standard, non-returnable.



Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)