



| Date | SYM | REVISION RECORD | AUTH | DR. | CK. |
|----------|-----|--------------------------------|------|------|-----|
| 12/14/12 | Α | REDRAWN IN AUTOCAD | T.B. | B.S. | |
| 5/31/13 | В | UPDATED TO ROHS 2 COMPLIANT | T.B. | B.S. | |
| | | | | | |
| | | | | | |
| | | | | | |





NOTES:

SPECIFICATION:

1. MATERIAL:

HOUSING: BLACK POLYPROPYLENE

FLAMMABILITY RATING -UL94-HB, UL FILE NO. E216959

TEMPERATURE RANGE: -10°C to +100°C

RIVETS: BRASS, NICKLE PLTD. WIRE: 26 AWG, 152.4mm LONG

SPRING: SPRING STEEL, NICKLE PLTD.

CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER

EIA-540J000

ROHS 2 COMPLIANT

| Tolerance (Except as noted) | MPD Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735 | | | | | | |
|-----------------------------|---|------------|--------|------------------|--|--|--|
| decimal | | | Scale | Drawn By B.S. | | | |
| ±.5 (.020) | | | | Approved By T.B. | | | |
| Fractional ± .8 (.030) | Title 4 "D" CELL HOLDER WITH WIRE LEADS | | | | | | |
| Angular | Date | Drawing Nu | mber | | | | |
| ± 3° | 5/31/13 | | BC24DW | | | | |