

INTER CONNECTION SCHEMATIC

| Date | SYM | REVISION RECORD | AUTH | DR. | CK. |
|----------|-----|--------------------------------|------|------|-----|
| 12/26/03 | A | Changed Material Specification | T.B. | B.S. | |
| 03/29/13 | B | Updated to "ROHS 2 COMPLIANT" | T.B. | B.S. | |
| | | | | | |
| | | | | | |
| | | | | | |


MOUNTING INSTRUCTION:

USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

NOTES:

MATERIAL:

- HOUSING: IMPACT RESISTANCE NYLON #6, BLACK, UL 94V-0, MATERIAL FILE #UL E 48285
- SPRING: SPRING STEEL, NICKLE PLATED
- CONTACTS: SPRING STEEL, NICKLE PLATED
- EYELETS: BRASS, NICKLE PLTD.
- JUMPER: #24 AWG, 2.5" LONG
- TERMINALS: BRASS, NICKLE PLTD., SNAP FASTENER MALE/FEMALE TERMINALS
- ROHS 2 COMPLIANT

| | | | |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|------------------|
| Tolerance (Inches) |  Memory Protection Devices, Inc. 200 Broad Hollow Road, Farmingdale, New York 11735 | | |
| Decimal | | Scale | Drawn By B.S. |
| ±.5 (.020) | | | Approved By T.B. |
| Fractional | Title | | |
| ± .8 (.030) | 3AA BATTERY HOLDER WITH SNAP FASTENERS | | |
| Angular | Date | Drawing Number | |
| ± 3° | 03/29/13 | BH3AA-SF | |