



INTER CONNECTION SCHEMATIC

1. MATERIAL:

HOUSING : HIGH IMPACT NYLON 66, HALOGEN AND PHOSPHOR FREE, UL94V-0, UL FILE NO. E48285

RIVETS: BRASS, NICKLE PLATED.

SPRING: 302 STAINLESS STEEL, NICKLE PLATED.

TEMPERATURE RANGE: -40°C TO +140°C

9 VALTS SNAPS: BRASS NICKEL PLATED

ESISTANT TO SOLVENTS, COMMON OILS AND REFRIGERANTS
ROHS 2 COMPLIANT

MOUNTING INSTRUCTION:

USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT. ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
12/26/03	A	CHANGED MATERIAL SPECIFICATION	T.B.	B.S.	
4/05/13	B	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	

Tolerance (Inches)	<div><div><div></div><div>MPD</div></div><div>Memory Protection Devices, Inc</div><div>200 Broad Hollow Road, Farmingdale, New York 11735</div></div>			
Decimal ±.5 (.020)			Scale	Drawn By B.S.
				Approved By T.B.
Fractional ± .8 (.030)	Title 4AA BATTERY HOLDER WITH SNAP FASTENERS			
Angular ± 3°	Date 4/05/13	Drawing Number BH4AA-SF		