

BOLT HOLE BRAKE CASTERS

BOLT HOLE BRAKE CASTERS

CASBRBHB, CASERBHB, CASNYBHB,
CASPUBHB

- Allows customization of applications by using a bolt in your choice of length or thread
- To attach the bolt, remove the wheel from the caster; attach the caster bracket to device and reassemble the caster
- Caster is totally immobile when the brake is applied
- Brake applied with an easy step on the locking pad



Nylon



Polyurethane



Black Rubber



Elastic Rubber

Standard Pack: 4 per bag								
Part No.	Material	Approx. Load Capacity Lbs.	Duty	Nominal Ø	Wheel Width	"H" Overall Height	Bolt Hole	Wheel Bearing
CASBRBHB05A	Black Rubber	88	Light	3.0 (76.2)	.90 (22.9)	3.77 (95.8)	Ø1.25 (31.8)	Roller Bearing
CASBRBHB10A		132	Light	4.0 (101.6)	1.06(26.9)	5.03 (127.8)	Ø1.45 (36.8)	
CASBRBHB15A		220	Medium	5.0 (127)	1.33 (33.8)	5.98 (151.9)	Ø1.37 (34.8)	
CASERBHB05A	Elastic Rubber	88	Light	3.0 (76.2)	1.29 (32.8)	3.97 (100.8)	1.10 X1.57 (27.9 X39.9)	Roller Bearing
CASERBHB10A		132	Light	4.0 (101.6)	1.29 (32.8)	5.07 (128.8)	1.10 X1.57 (27.9 X39.9)	
CASERBHB15A		220	Medium	5.0 (127)	1.33 (33.8)	6.10 (154.9)	1.10 X1.57 (27.9 X39.9)	
CASNYBHB05A	Nylon	176	Medium	3.0 (76.2)	.86 (21.8)	3.97 (100.8)	Ø.41 (10.4)	Plain
CASNYBHB10A		220	Medium	4.0 (101.6)	1.02 (25.9)	5.19 (131.8)	Ø.50 (12.7)	
CASPUBHB05A		176	Medium	3.0 (76.2)	1.25 (31.8)	3.97 (100.8)	1.10 X1.57 (27.9 X39.9)	
CASPUBHB10A	Polyurethane	264	Medium	4.0 (101.6)	1.25 (31.8)	5.07 (128.8)	1.10 X1.57 (27.9 X39.9)	Precision Ball Bearing
CASPUBHB15A		330	Medium	5.0 (127)	1.25 (31.8)	6.10 (154.9)	1.10 X1.57 (27.9 X39.9)	