



Model #: BP72V28-3UNAFTA

External Battery Pack for UPS System - NAFTA assembled version of BP72V28RT-3U



Highlights

- Extends the runtime of select compatible Tripp Lite UPS systems with 72VDC external battery connector
- Simple installation; 3U rackmount, tower and stack adaptable
- 2-year warranty

Description

BP72V28-3UNAFTA rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation. Additional DC connector enables the daisy-chaining of multiple external battery packs for longer extended run capability. COMPATIBLE UPS SYSTEMS - SU3000RMNAFTA, SU3000XLNAFTA, and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

• Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP72V28-3UNAFTA external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

Specifications

BATTERY		
Expandable battery runtime	Yes, DC connector accepts daisy-chaining of multiple external battery packs for extended runtime operation	

DC system voltage (VDC)	72		
Connects to UPS via	Black 3-point battery connector		
Typical battery lifespan	4-6 years typical		
PHYSICAL	PHYSICAL		
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5		
Shipping Dimensions (HWD/cm)	28.58 x 58.42 x 80.01		
Shipping weight (lbs)	203.9		
Shipping weight (kg)	92.57		
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25		
Unit Dimensions (HWD/cm)	13.33 x 44.45 x 63.5		
Unit weight (lbs)	166.45		
Unit weight (kg)	75.57		
Material of construction	Steel		
Form factors supported	3U rack/tower		

Related Items

Optional Products

Related Model	Description	Qty.
WEXT3-BP72V	3-Year Extended Warranty - For All 72V Battery Packs	1
WEXT5-BP72V	5-Year Extended Warranty - For All 72V Battery Packs	1
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
2POSTRMKITWM	Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=3544.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.