

Part Number    **BRR.0S.200.PZSG**

Size/Series 0S / S

[Request a quote](#)


## MECHANICAL DETAILS

|                          |                                                                                               |
|--------------------------|-----------------------------------------------------------------------------------------------|
| <b>Shell Style/Model</b> | BRR*: Cap spring loaded dust cap for ERA,ERN and EG receptacle or PSA and PK fixed receptacle |
| <b>Keying</b>            |                                                                                               |
| <b>Housing Material</b>  | POM (Polyoxymethylene) shell without treatment, silicone gasket                               |
| <b>Cable Fixing</b>      | $\perp$ : 0 - 0 mm                                                                            |
| <b>Variant</b>           | :                                                                                             |

## PERFORMANCE DETAILS

## OTHER CHARACTERISTICS

|                              |                            |
|------------------------------|----------------------------|
| <b>Endurance (Shell)</b>     | 3839 mating cycles         |
| <b>Humidity (max):</b>       | <=95% [at 60 deg C /140 F] |
| <b>Vibration:</b>            | 15 g [10 Hz - 2000 Hz]     |
| <b>Shock Resistance:</b>     | 100 g [ 6 ms]              |
| <b>Salt Spray Corrosion:</b> | >144 hr                    |
| <b>Climatical Category:</b>  | 50/175/21                  |
| <b>Shielding (min):</b>      | 75 dB (10 MHz)             |
| <b>Shielding (min):</b>      | 40 dB (1 GHz)              |
| <b>IP Rating</b>             | 50                         |
| <b>Catalog</b>               |                            |

[Copyright](#) [Privacy policy](#) [Product safety](#)

