

MICRO SWITCH

FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH - ENCLOSED

CATALOG LISTING
BZE6-2RN191-S

BZE6-2RN191-S

M

DRAWING
NUMBER

7

ISSUE

REPLACES

PR-15095

29AUG07

PSR

CHECK

24AUG06

DVM

CHECK

24AUG06

E

0025947

KNS

30OCT06

F

0033014

BS

29AUG07

CHECK

23 SEPT 86

JAS

23 SEPT 86

REVISIONS

A	0072476	HAM	4 SEP 92
B	0072476	CO	17 FEB 94
C	0017057	KDR	17 FEB 94
D	0023923	VKR	23 NOV 05
E	0025947	RKP	24AUG06
F	0033014	BS	29AUG07

MASTER
FO-32851-B

DRAWN

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA
OPERATING FORCE ----- 15 - 39 OZ	CONTACT ARRANGEMENT S P D T
RELEASE FORCE ----- 10 OZ MIN	L74
DIFFERENTIAL TRAVEL ----- .002 MAX	15A 125, 250, OR 480VAC 2A 600 VAC
OVERTRAVEL ----- .219 MIN	1/8 HP 125 VAC, 1/4 HP 250 VAC
BASIC SWITCH REPLACEMENT--BZ-2RN7191	1/2A 125 VDC, 1/4A 250 VDC
	CE 1.5A, 240 Vac

SCALE FULL
DO NOT SCALE PRINT
TOLERANCES APPLY TO DIMENSIONS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±
NO PLACES ONE PLACE TWO PLACES THREE PLACES ANGLES
DESIGN UNITS THIRD ANGLE PROJECTION
WEIGHT .56 LB

NOTES

- 1 - 6-32 UNC X .219 REF BINDING HEAD TERMINAL SCREW AND CUPWASHER(3)
- 2 - FURNISHED UNASSEMBLED
- 3 - SEAL RATING: NEMA 1,3,4
IP66

