

Part Number: C0432A

Revision: 10/31/2012

3C 22 AWG (7/30)TC PVC, PVC**COMMUNICATION & CONTROL CABLE****A. CONSTRUCTION**

Conductor:	#22 AWG (7/30) Tinned Copper	.029" Nom
Insulation:	.013" Wall, Polyvinyl Chloride (PVC)	.055" Nom
Cable Core:	3C @ 4.00" LHL	.112" Nom
Jacket:	.036" Wall, Polyvinyl Chloride (PVC)	.184" Nom
Print Legend:	<i>CAROL (R) 22 AWG -- C0432A -- 105C TYPE PLTC E60233-8 (UL) -- 105C CSA LL69381 CMG FT4 -- ROHS -- MADE IN USA (DATE CODE) (SEQUENTIAL FOOTAGE)</i>	

DIAMETERS**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 13	PLTC
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +105°C
Suggested Working Voltage:	300V Max
Conductor DCR:	17.5 Ohms/1000 ft @ 20°C (max)
Mutual Capacitance:	27.4 pF/ft @ 1kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED
3	WHITE