

Part Number: C0651A

Revision Level: 00

Date: June 17, 2005

3P 22 7/30 TC SR-PVC OAS PVC**COMPUTER CABLE****A. CONSTRUCTION****DIAMETERS**

1)	CONDUCTOR:	#22 AWG 7/30 Tinned Copper	0.030" nom.
2)	INSULATION:	0.010" Wall Semi Rigid Polyvinyl Chloride	0.050" nom.
3)	COLOR CODE:	1. Black-Red 2. Black-White 3. Black-Green	
4)	PAIRING:	6 Conductors into 3 Pairs @ 2" LHL	0.100" nom.
5)	CABLE:	3 Pairs @ 2.50" LHL with aluminum/polypropylene (foil out)	0.200" nom.
6)	BRAID:	Tinned Copper Braid 65% Nom. Coverage	0.232" nom.
7)	JACKET:	0.032" Wall Polyvinyl Chloride - Gray	0.296" +/- 0.015"
8)	PRINT LEGEND:	<i>CAROL (R) 22 AWG -- C0651A -- 75C E111240-8 CMR(UL)C(UL) OR 80C AWM STYLE 2464 300V --- CSA LL69381 CMG - MADE IN USA (DATE CODE- - PRINT EVERY 3 FEET)</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CMR(UL)C(UL)
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

1)	TEMPERATURE:	75 C
2)	SUGGESTED WORKING VOLTAGE (Vrms):	300 Vrms
3)	CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft. nom. @ 20 C
4)	SHIELD RESISTANCE:	4.1 Ohms/1000 ft. nom. @ 20 C
5)	MUTUAL CAPACITANCE:	28.6 pF/ft. @ 1kHz nom.
6)	GROUND CAPACITANCE:	51.5 pF/ft. @ 1kHz nom.
7)	CHARACTERISTIC IMPEDANCE:	69 Ohms @ 1 MHz nom.

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.