

Part Number: C0832A Revision Level: 1 Date: 10/24/2007

5P 24 AWG 7/32 TC PE OAS PVC

Computer Cable

A. CONSTRUCTION

DIAMETERS

Conductor:	#24 AWG 7/32 Tinned Copper	0.024" nom.
Insulation:	0.015" Wall Polyethylene	0.054" nom.
Pairing	2 conductors @ 2.00" LHL	0.108" nom.
Cable:	5P @ 2.00" LHL with AL / PE tape & 24 AWG 7/32 TC DW	0.272" nom.
Braid	# 36 AWG Tinned Copper 90% Coverage	0.274" nom.
Jacket:	0.032" Wall Polyvinyl Chloride - Gray	0.338" +/- 0.017"
Print Legend:	<i>CAROL (R) 24 AWG -- C0832A -- 75C E111240-8 CM (UL) C (UL) CMH OR 80C AWM STYLE 2919 30V LOW VOLTAGE COMPUTER CABLE - - MADE IN USA (DATE CODE) (PRINT</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM(UL)c(UL) CMH
UL Subject 758	AWM Style 2919
CSA International	Type CM(UL)c(UL) CMH

C. ELECTRICAL PROPERTIES

TEMPERATURE:	80C
SUGGESTED WORKING VOLTAGE (V _{rms}):	30V
CONDUCTOR D.C. RESISTANCE:	25.7 Ohms/1000 ft nom
SHIELD RESISTANCE:	1.9 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	14.19 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	25.54 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	108.8 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow