

Part Number: C1702

Revision Level: 11/19/2012

2C 14AWG 41/30BC PP, PVC**COMMAND® SERIES****A. CONSTRUCTION**

Conductor:	14 AWG 41/30 BC	.071" nom
Insulation:	.009" Wall, Polypropylene (PP)	.089" nom
Cable Core:	2C @ 6.00" LHL	.178" nom
Jacket:	.030" Polyvinyl Chloride (PVC)	.238" nom
Print Legend:	CAROL® -- C1702 -- 2C 14AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8 CL3 60C -- CSA LL69381 AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage)	

DIAMETERS**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	2.56 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	23.3 pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____
Date: _____