

Part Number: C1803

Revision Level: 11/19/2012

4C 14 AWG (105/34) OFHC BC PP, PVC**COMMAND® SERIES****A. CONSTRUCTION**

Conductor: 14 AWG 105/34 BC .074" nom
Insulation: .009" Wall, Polypropylene (PP) .092" nom
Cable Core: 4C @ 3.50" LHL .223" nom
Jacket: .030" Polyvinyl Chloride (PVC) .283" nom
Print Legend: **CAROL® -- C1803 -- COMMAND OFHC HD 14AWG 4C ROHS -- 75C E60233-8 (UL)
CL3 -- LL69381 CSA AWM I/II A/B 80C 600V FT4 -- MADE IN USA
(Date code) (Seq Footage)**

DIAMETERS**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	2.62 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	23.8pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____
Date: _____