

Part Number: C2015A

Revision Level: 02

Date: May 18, 2006

1C 24 7/32 TC PVC INS

HOOK-UP WIRE

A. CONSTRUCTION

DIAMETERS

- | | | |
|------------------|--|-------------------|
| 1) CONDUCTOR: | #24 AWG 7/32 Tinned Copper | 0.024" nom. |
| 2) INSULATION: | 0.016" Wall Polyvinyl Chloride | 0.056" +/- 0.003" |
| 3) PRINT LEGEND: | <i>CAROL A 24 AWG RU AWM 80C VW-1 E18621-8 --- CSA LL69381 TR64 90C --
-MADE IN USA</i> | |

B. INDUSTRY APPROVALS

UL Subject 758

AWM Style 1007, 1569

CSA International

Type TR64

C. ELECTRICAL PROPERTIES

- | | |
|--------------------------------------|--------------------------------|
| 1) TEMPERATURE: | 80 C (UL); 90C (CSA) |
| 2) SUGGESTED WORKING VOLTAGE (Vrms): | 300Vrms |
| 3) CONDUCTOR D.C. RESISTANCE: | 25.7 Ohms/1000 ft. nom. @ 20 C |

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.