

Part Number: C3129 Revision Level: 0 Date: 7/7/2007

2C 12 19/0.0185 BC FLEX FLEX

TYPE CL3P

A. CONSTRUCTION

DIAMETERS

Conductor:	#12 AWG 19/0.0185 Bare Copper	0.092" nom.
Insulation:	0.010" Wall FLEXGUARD*	0.112" nom.
Cable:	2 Conductors @ 4.00" LHL.	0.184" nom.
Jacket:	0.015" Wall FLEXGUARD* - Natural	0.214" +/- 0.011"
	-Plenum ripcord under jacket.	
Print Legend:	CAROL (R) 12 AWG -- C3129 -- 75C E60233-8 (UL) CL3P -- MADE IN USA	
	DATE CODE (PRINT EVERY 2 FT)	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3P

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	150 Vrms (CL3P)
CONDUCTOR D.C. RESISTANCE:	1.6 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White