

General Cable Product Data Sheet

Part Number: C3193

Revision Level: 0

Date: 7/7/2007

2C 16 19/.0117 BC FLEX PVDF

TYPE CL2P / CMP

A. CONSTRUCTION

DIAMETERS

Conductor: #16 AWG 19/.0117 Bare Copper

0.056" nom.

Insulation: 0.008" Wall FLEXGUARD*

0.072" nom.

Cable: 2 Conductors @ 4.00" LHL.

0.121" nom.

Jacket: 0.010" Wall PVDF – Natural

0.141" +/- 0.007"

-Plenum ripcord under jacket.

Print Legend: **CAROL (R) 16 AWG -- C3193 -- 60C E60233-8 CL2P OR CMP(UL) C(UL) -- MADE IN USA
DATE CODE (PRINT EVERY 2 FT)**

B. INDUSTRY APPROVALS

National Electrical Code

Article 725

UL Standard 13

Type CL2P

National Electrical Code

Article 800

UL Standard 444

Type CMP

C. ELECTRICAL PROPERTIES

TEMPERATURE:

60C

SUGGESTED WORKING VOLTAGE (Vrms):

150 Vrms (CL2P); 300 Vrms (CMP)

CONDUCTOR D.C. RESISTANCE:

4.1 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.