

General Cable Product Data Sheet

Part Number: C3241

Revision Level: 1

Date: 10/26/2007

2C 16 SOLID BC HALAR PVC

Fire Alarm/Life Safety Cable

A. CONSTRUCTION

DIAMETERS

Conductor:	#16 AWG Solid Bare Copper	0.051" nom.
Insulation:	0.016" Wall Halar	0.083" nom.
Cable:	2C @ 4.00" LHL	0.166" nom.
Jacket:	0.015" Wall FLEXGUARD* - Red	0.196" +/- 0.01"
Print Legend:	<i>E86522-F CAROL CABLE TYPE FPLP 16 AWG -- C3241 -- (UL) -- MID-CAP --- (seq. Footage mks every 2 ft. in ascending order) i.e. 000003, 000006, etc.</i>	

B. INDUSTRY APPROVALS

National Electrical Code
UL Standard 1424

Article 760
Type FPLP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V
CONDUCTOR D.C. RESISTANCE:	4.2 Ohms/1000 ft nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.