

Part Number: C4008A

Revision: 10/31/2012

1PR 22 AWG (SOLID)TC SRPVC, PVC**COMMUNICATION & CONTROL CABLE****A. CONSTRUCTION**

Conductor:	#22 AWG (Solid) Tinned Copper	.025" Nom
Insulation:	.010" Wall, Semi-Rigid Polyvinyl Chloride (SR-PVC)	.044" Nom
Cable Core:	2C @ 6.00" LHL	.088" Nom
Jacket:	.031" Wall, Polyvinyl Chloride (PVC)	.150" Nom
Print Legend:	<i>CAROL (R) 22 AWG -- C4008A -- 75C E105765-H CM (UL) C(UL) OR AWM STYLE 2464 -- CSA LL69381 CMG 60C -- MADE IN USA (DATE CODE) (SEQUENTIAL FOOTAGE)</i>	

DIAMETERS**B. INDUSTRY APPROVALS**

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +75°C
Suggested Working Voltage:	300V Max
Conductor DCR:	17.5 Ohms/1000 ft @ 20°C (max)
Mutual Capacitance:	25.0 pF/ft @ 1kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED