

Part Number: C4100A

Revision Date: 12/11/2012

2C 22 (7/30)TC PVC, PVC**COMMUNICATION AND CONTROL CABLE****A. CONSTRUCTION**

Conductor: #22AWG (7/30) Tinned Copper
Insulation: .010" Wall, Polyvinyl Chloride (PVC)
Cable Core: Cable 2 conductors @ 6.00" LHL

Jacket: .032" Polyvinyl Chloride (PVC) jacket

Print Legend: **CAROL ® 22 AWG -- C4100A -- CSA C/US LL69381 CMG 105C OR AWM I/II A/B 105C 600V FT4 -
- RU AWM STYLE 2464 80C 300V -- MADE IN USA
(DATE CODE) (SEQUENTIAL FOOTAGE)**

DIAMETERS

.029" nom

.049" Nom

.098" Nom

.162" Nom

B. INDUSTRY APPROVALS

UL Standard 758

AWM Style 2464

CSA International C22.2 No214

Type CMG

CSA International C22.2 No210

Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature: -20°C TO +105°C

Suggested Working Voltage: 600V

Conductor DCR: 16.89 Ohms/M' @ 20°C (Max)

Mutual Capacitance: 30.6 pF/ft. @ 1 kHz (Nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____

Date: _____