

Part Number: C4192A

Revision Date: 10/29/2012

2C 22 AWG 7/30 TC PVC / OAS / PVC
COMMUNICATION & CONTROL CABLE
A. CONSTRUCTION

Conductor: #22 AWG 7/30 Tinned Copper
 Insulation: .009" Polyvinyl Chloride (PVC)
 Cable Core: Cable 2/C @ 1.25" LHL
 Shield: 22AWG 7/30 TC Drain wire, Aluminum / Polyester foil facing out, 100% coverage
 Jacket: .032" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"

DIAMETERS

.029" Nom
 .047" Nom
 .099" Nom
 .155" to .171"

Print Legend:

CAROL (R) 24 AWG--C4191A--CSA C/US LL69381 CMG
105C OR CSA AWM I/II A/B 105C 600V FT4 --- ~RU~
AWM STYLE 2464 80C 300V --- MADE IN USA
(DATE CODE) (SEQUENTIAL FOOTAGE)

B. INDUSTRY APPROVALS
FILE #

UL Standard 758	AWM Style 2464	E18621
CSA International	Type CMG	LL69381
CSA International	AWM I/II A/B	

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to 105°C
Suggested Working Voltage:	300V
Conductor DCR:	16.9 Ohms/M' @ 20°C
Mutual Capacitance:	52.4 pF/ft. @ 1 kHz

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____