

Part Number: C6061A

Revision Level: 10/31/2012

**3 Individually shielded pairs 20AWG PP/ PE****DIRECT BURIAL, AUDIO & COMMUNICATION****A. CONSTRUCTION**

Conductor: 20 AWG 10/30TC  
Insulation: .013" Wall, Polypropylene (PP)  
Pair: Twist 2 conductors with a 2.00" LHL  
Shield: Clear Polyester, 24 AWG 7/32TC Drain wire,  
Aluminum / Polyester foil facing in over each pair  
Cable Core: 3PR @ 6.00" LHL  
Jacket: .0475" Wall, Polyethylene (PE)  
Print Legend: **No print**

**DIAMETERS**

.038" nom  
.064" nom  
  
  
  
.245" nom  
.340" nom

**B. INDUSTRY APPROVALS**

720 Hour sunlight resistant per UL 1581 / 2556

**C. ELECTRICAL PROPERTIES**

Temperature: -20°C to 80°C  
Suggested Working Voltage: 350V  
Conductor DCR: 10.9 Ohms/M' @ 20°C  
Mutual Capacitance: 26 pF/ft @ 1kHz nom

**D. COLOR CODE**

| PAIR | COLOR       |
|------|-------------|
| 1    | BLACK / RED |
| 2    | BLACK / WHT |
| 3    | BLACK / GRN |