

Part Number: C7110A

Revision: 4/25/2013

4C 22 AWG (19/34)TC PE OAS PVC
COMMUNICATION & CONTROL CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#22 AWG (19/34) Tinned Copper	.032" Nom
Insulation:	.016" Wall, Polyethylene (PE)	.064" Nom
Cable:	4C @ 1.75" LHL	
Shield:	Aluminum/Polyester Tape (Foil Out) with (1) #25 AWG stranded TCCS + (3) #23 AWG solid TCCS Drain Wires	.160" Nom
Jacket:	.051" Wall, Polyvinyl Chloride (PVC)	.262" Nom
Print Legend:	<i>CAROL A (R) 22 AWG -- C7110A -- 75C E60233-8 CL3 (UL) OR 60C AWM STYLE 2094 300V -- CM (UL) C(UL) -- MADE IN USA (DATE CODE) (SEQUENTIAL FOOTAGE) (PRINTED EVERY 2 FEET)</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3
National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2094

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +75°C
Suggested Working Voltage:	300V max
Conductor DCR:	14.45 Ohms/1000 ft @ 20°C (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED
3	GREEN
4	NATURAL (TRANSLUCENT)

E. CUSTOMER APPROVAL

Signature: _____
Date: _____