

Description: Tinned Copper conductor, FEP Insulation, Individually shielded pairs, and overall FEP Jacketed Plenum Cable.


A. Construction:

- 1.0 Primaries:
- 1.1 Conductor: 22 AWG
Stranding 7/30 Tinned Copper;
Nom. Dia .030"
- 1.2 Insulation: FEP
Material FEP
Nom. thickness .006"
Nom. OD .042"
- 2.0 Pair construction: Two insulated conductors twisted together
- 2.1 Shield: Aluminum/Polyester Tape; 100% coverage; (Aluminum Side IN)
- 2.2 Drain Wire: 24 AWG (7/32) Tinned Copper
- 2.3 No. of Pairs 2
- 2.4 Pair Color Code: Black & Red Green & White
- 3.0 Overall Cabling: Two pairs cabled
- 4.0 Jacket Material: FEP Nom. wall: .014" Color: TBD
- 5.0 Overall Diameter of Cable Nom. .186"
- 6.0 Marking: Surface Print:
GENERAL CABLE (F) C8112 2PR 22 AWG SHIELDED CMP (UL) C(UL) ---- ROHS
AAAAA*
* Indicates Shop Order number

B. Characteristics:

- 1.0 Conductor DC Resistance @20C Max. (Ohm): 16
- 2.0 Capacitance between conductors Nom. (pF/ft): 35
- 3.0 Capacitance Cond. To other Cond. & Shield Nom. (pF/ft): 65
- 4.0 Shield resistance Nom. (ohms/1000 ft): 15
- 5.0 Characteristic Impedance Nom. (Ohms): 40
- 6.0 Velocity of Propagation Nom. : 67
- 7.0 Operating Voltage Nom.: 300 V
- 8.0 Continuous Operating Temp: 200C
- 9.0 Min. Bend Radius (inches): 1.9
- 10.0 Max. Pulling Tension Lbs: 46

C. Approvals: UL –CMP ; C(UL) CMP

R E V	DATE	CHANGE DETAIL	 General Cable		General Cable 20 Forge Park, Franklin, Ma 02038 Phone: 508-541-7100 Fax: 508-541-8122		
			Title:	C8112			
			Description:	2 PR 22 AWG Shielded Plenum Cable			
			Created By:				
A	07/02/09	Initial Release -DB	Final Approval:	VM – 7/2/09		PAGE 1 of 1	