

Part Number: C9035A

Revision Date:

9/4/2012

15C 18 AWG 16/30 TC PVC / PVC


A. CONSTRUCTION

Conductor: #18 AWG 16/30 Tinned Copper
 Insulation: .016" Polyvinyl Chloride (PVC)
 Cable Core: Cable 15/C @ 5.50" LHL w/ clear polyester wrap, 100% coverage
 Jacket: ".032"" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"

DIAMETERS

.046" Nom
 .078" Nom
 .372" Nom
 .436" Nom

Print Legend: **CAROL® EXZEL™ -- C9035A -- 15C 18 AWG**
E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V
VW-1 --- LL69381 CSA TYPE CMG 105C FT4 -- CE --
-- ROHS -- MADE IN USA
(DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	6.81 Ohms/M' @ 20°C
Mutual Capacitance:	24.4 pF/ft. @ 1 kHz Nom

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN
5	ORANGE
6	BLUE
7	BROWN
8	YELLOW
9	PURPLE
10	GRAY

COLOR CODE

ITEM	COLOR
11	PINK
12	TAN
13	RED with GREEN stripe
14	RED with YELLOW stripe
15	RED with BLACK stripe