BC857B

SMALL SIGNAL PNP TRANSISTOR

PRELIMINARY DATA

Type	Marking
BC857B	3F

- SILICON EPITAXIAL PLANAR PNP TRANSISTOR
- MINIATURE SOT-23 PLASTIC PACKAGE FOR SURFACE MOUNTING CIRCUITS
- TAPE AND REEL PACKING
- THE NPN COMPLEMENTARY TYPE IS BC847B

APPLICATIONS

- WELL SUITABLE FOR PORTABLE EQUIPMENT
- SMALL LOAD SWITCH TRANSISTOR WITH HIGH GAIN AND LOW SATURATION VOLTAGE



SOT-23

INTERNAL SCHEMATIC DIAGRAM



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage (I_E = 0)	-50	V
V_{CEO}	Collector-Emitter Voltage (I_B = 0)	-45	V
V_{EBO}	Emitter-Base Voltage (I_C = 0)	-5	V
I_C	Collector Current	-100	mA
I_{CM}	Collector Peak Current	-200	mA
P_{tot}	Total Dissipation at T_C = 25 °C	250	mW
T_{stg}	Storage Temperature	-65 to 150	°C
T_j	Max. Operating Junction Temperature	150	°C

THERMAL DATA

$R_{thj\text{-}amb}$ •	Thermal Resistance Junction-Ambient	Max	500	$^oC/W$

• Device mounted on a PCB area of 1 cm^2.

ELECTRICAL CHARACTERISTICS (T_{case} = 25 ^oC unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{CBO}	Collector Cut-off Current (I_E = 0)	V_{CB} = -30 V V_{CB} = -30 V T_C = 150 ^oC		-1	-15 -5	nA µA
I_{EBO}	Emitter Cut-off Current (I_C = 0)	V_{EB} = -5 V			-100	nA
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage (I_E = 0)	I_C = -10 µA	-50			V
$V_{(BR)CEO}$*	Collector-Emitter Breakdown Voltage (I_B = 0)	I_C = -2 mA	-45			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage (I_C = 0)	I_E = -10 µA	-5			V
$V_{CE(sat)}$*	Collector-Emitter Saturation Voltage	I_C = -10 mA I_B = -0.5 mA I_C = -100 mA I_B = -5 mA		-0.07 -0.25	-0.3 -0.65	V V
$V_{BE(sat)}$*	Base-Emitter Saturation Voltage	I_C = -10 mA I_B = -0.5 mA I_C = -100 mA I_B = -5 mA		-0.7 -0.85		V V
$V_{BE(on)}$*	Base-Emitter On Voltage	I_C = -2 mA V_{CE} = -5 V I_C = -10 mA V_{CE} = -5 V	-0.6	-0.65	-0.75 -0.82	V V
h_{FE}	DC Current Gain	I_C = -2 mA V_{CE} = -5 V	220		475	
f_T	Transition Frequency	I_C = -10 mA V_{CE} = -5 V f = 100MHz	100			MHz
C_{CBO}	Collector-Base Capacitance	I_E = 0 V_{CB} = -10 V f = 1 MHz		4.5		pF
NF	Noise Figure	V_{CE} = -5 V I_C = -0.2 mA f = 1KHz Δf = 200 Hz R_G = 2 KΩ		2	10	dB

* Pulsed: Pulse duration = 300 µs, duty cycle ≤ 2 %

SOT-23 MECHANICAL DATA

DIM.	mm			mils		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	0.85		1.1	33.4		43.3
B	0.65		0.95	25.6		37.4
C	1.20		1.4	47.2		55.1
D	2.80		3	110.2		118
E	0.95		1.05	37.4		41.3
F	1.9		2.05	74.8		80.7
G	2.1		2.5	82.6		98.4
H	0.38		0.48	14.9		18.8
L	0.3		0.6	11.8		23.6
M	0		0.1	0		3.9
N	0.3		0.65	11.8		25.6
O	0.09		0.17	3.5		6.7