




2N720A

EPITAXIAL PLANAR NPN

■ HIGH VOLTAGE GENERAL PURPOSE


DESCRIPTION

The 2N790A is a silicon Planar Epitaxial NPN transistor in Jedec TO-18 metal case. It is suitable for a wide variety of amplifier and switching applications.



TO-18

INTERNAL SCHEMATIC DIAGRAM



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage ($I_E = 0$)	120	V
V_{CEO}	Collector-Emitter Voltage ($I_B = 0$)	80	V
V_{EBO}	Emitter-Base Voltage ($I_C = 0$)	7	V
I_C	Collector Current	500	mA
P_{tot}	Total Dissipation at $T_{amb} \leq 25\text{ }^{\circ}\text{C}$ at $T_C \leq 25\text{ }^{\circ}\text{C}$	0.5 1.8	W W
T_{stg}	Storage Temperature	-55 to 175	$^{\circ}\text{C}$
T_j	Max. Operating Junction Temperature	175	$^{\circ}\text{C}$

2N720A

THERMAL DATA

R _{thj-case}	Thermal Resistance Junction-Case	Max	83.3	°C/W
R _{thj-amb}	Thermal Resistance Junction-Ambient	Max	300	°C/W


ELECTRICAL CHARACTERISTICS (T_{case} = 25 °C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I _{CBO}	Collector Cut-off Current (I _E = 0)	V _{CB} = 90 V			10	nA
V _{(BR)CBO}	Collector-Base Breakdown Voltage (I _E = 0)	I _C = 100 µA	120			V
V _{(BR)CEO} *	Collector-Emitter Breakdown Voltage (I _B = 0)	I _C = 30 mA	80			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage (I _C = 0)	I _E = 100 µA	7			V
I _{EBO}	Emitter Cut-off Current (I _E = 0)	V _{EB} = 5 V			10	nA
V _{CE(sat)} *	Collector-Emitter Saturation Voltage	I _C = 50 mA I _C = 150 mA	I _B = 5 mA I _B = 15 mA		1.2 5	V V
V _{BE(sat)} *	Base-Emitter Saturation Voltage	I _C = 50 mA I _C = 150 mA	I _E = 5 mA I _E = 15 mA		0.9 1.3	V V
h _{FE} *	DC Current Gain	I _C = 100 µA I _C = 10 mA I _C = 150 mA	V _{CE} = 10 V V _{CE} = 10 V V _{CE} = 10 V	20 35 40	120	
h _{fe} *	Small Signal Current Gain	I _C = 50 mA f = 20 MHz	V _{CE} = 10 V	2.5		
C _{CBO}	Collector-Base Capacitance	I _E = 0 V _{CB} = 10 V f = 1 MHz			15	pF
C _{EBO}	Emitter-Base Capacitance	I _C = 0 V _{EB} = 0.5 V f = 1 MHz			85	pF

* Pulsed: Pulse duration = 300 µs, duty cycle ≤ 1 %

TO-18 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A		12.7			0.500	
B			0.49			0.019
D			5.3			0.203
E			4.9			0.193
F			5.8			0.228
G	2.54			0.100		
H			1.2			0.047
I			1.16			0.045
L	45°			45°		



Obsolete Product(s) - Obsolete Product(s)
Obsolete Product(s) - Obsolete Product(s)

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 2002 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>