


Thyristor

V_{RRM} = 1600V
 I_{TAV} = 23A
 V_T = 1.42V

Single Thyristor


Part number

CMA30E1600PN



Backside: Isolated

 E72873



Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability

Applications:


- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: TO-220FP

- Isolation Voltage: 2500 V~
- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0
- Soldering pins for PCB mounting
- Base plate: Plastic overmolded tab
- Reduced weight

Thyristor			Ratings			
Symbol	Definition	Conditions	min.	typ.	max.	Unit
$V_{RSM/DSM}$	max. non-repetitive reverse/forward blocking voltage	$T_{VJ} = 25^\circ C$			1700	V
$V_{RRM/DRM}$	max. repetitive reverse/forward blocking voltage	$T_{VJ} = 25^\circ C$			1600	V
I_{RD}	reverse current, drain current	$V_{RD} = 1600 V$ $V_{RD} = 1600 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		10 2	μA mA
V_T	forward voltage drop	$I_T = 30 A$ $I_T = 60 A$ $I_T = 30 A$ $I_T = 60 A$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		1.42 1.80 1.42 1.92	V V V V
I_{TAV}	average forward current	$T_C = 40^\circ C$	$T_{VJ} = 150^\circ C$		23	A
$I_{T(RMS)}$	RMS forward current	180° sine			36	A
V_{TO} r_T	threshold voltage slope resistance } for power loss calculation only		$T_{VJ} = 150^\circ C$		0.90 17	V $m\Omega$
R_{thJC}	thermal resistance junction to case				2.5	K/W
R_{thCH}	thermal resistance case to heatsink			0.50		K/W
P_{tot}	total power dissipation		$T_C = 25^\circ C$		50	W
I_{TSM}	max. forward surge current	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$ $t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$ $t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$ $t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$	$T_{VJ} = 45^\circ C$ $V_R = 0 V$ $T_{VJ} = 150^\circ C$ $V_R = 0 V$		260 280 220 240	A A
I^2t	value for fusing	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$ $t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$ $t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$ $t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$	$T_{VJ} = 45^\circ C$ $V_R = 0 V$ $T_{VJ} = 150^\circ C$ $V_R = 0 V$		340 325 240 240	A^2s A^2s A^2s A^2s
C_J	junction capacitance	$V_R = 400 V$ $f = 1 \text{ MHz}$	$T_{VJ} = 25^\circ C$		9	pF
P_{GM}	max. gate power dissipation	$t_p = 30 \mu s$ $t_p = 300 \mu s$	$T_C = 150^\circ C$		10 5 0.5	W W W
P_{GAV}	average gate power dissipation					
$(di/dt)_{cr}$	critical rate of rise of current	$T_{VJ} = 125^\circ C; f = 50 \text{ Hz}$ repetitive, $I_T = 90 A$ $t_p = 200 \mu s; di_G/dt = 0.2 A/\mu s;$ $I_G = 0.2 A; V_D = \frac{2}{3} V_{DRM}$ non-repet., $I_T = 30 A$			150	$A/\mu s$
$(dv/dt)_{cr}$	critical rate of rise of voltage	$V_D = \frac{2}{3} V_{DRM}$ $R_{GK} = \infty$; method 1 (linear voltage rise)	$T_{VJ} = 125^\circ C$		500	$V/\mu s$
V_{GT}	gate trigger voltage	$V_D = 6 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = -40^\circ C$		1.3 1.6	V V
I_{GT}	gate trigger current	$V_D = 6 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = -40^\circ C$		28 50	mA mA
V_{GD}	gate non-trigger voltage	$V_D = \frac{2}{3} V_{DRM}$	$T_{VJ} = 125^\circ C$		0.2	V
I_{GD}	gate non-trigger current				1	mA
I_L	latching current	$t_p = 10 \mu s$ $I_G = 0.2 A; di_G/dt = 0.2 A/\mu s$	$T_{VJ} = 25^\circ C$		90	mA
I_H	holding current	$V_D = 6 V$ $R_{GK} = \infty$	$T_{VJ} = 25^\circ C$		80	mA
t_{gd}	gate controlled delay time	$V_D = \frac{1}{2} V_{DRM}$ $I_G = 0.5 A; di_G/dt = 0.5 A/\mu s$	$T_{VJ} = 25^\circ C$		2	μs
t_q	turn-off time	$V_R = 100 V; I_T = 30 A; V_D = \frac{2}{3} V_{DRM}$ $T_{VJ} = 150^\circ C$ $di/dt = 10 A/\mu s; dv/dt = 20 V/\mu s; t_p = 200 \mu s$		150		μs

Package TO-220FP			Ratings			
Symbol	Definition	Conditions	min.	typ.	max.	Unit
I_{RMS}	RMS current	per terminal			35	A
T_{stg}	storage temperature		-55		150	°C
T_{VJ}	virtual junction temperature		-40		150	°C
Weight				2		g
M_D	mounting torque		0.4		0.6	Nm
F_c	mounting force with clip		20		60	N
$d_{Spp/App}$	creepage distance on surface striking distance through air	terminal to terminal	1.6	1.0		mm
$d_{Spb/Apb}$		terminal to backside	2.5	2.5		mm
V_{ISOL}	isolation voltage	t = 1 second t = 1 minute 50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA	2500 2080			V V

Product Marking**Part number**

C = Thyristor (SCR)
M = Thyristor
A = (up to 1800V)
30 = Current Rating [A]
E = Single Thyristor
1600 = Reverse Voltage [V]
PN = TO-220ABFP (3)

Ordering	Part Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	CMA30E1600PN	CMA30E1600PN	Tube	50	505254

Similar Part	Package	Voltage class
CMA30E1600PB	TO-220AB (3)	1600
CS22-12io1M	TO-220ABFP (3)	1200
CLA30E1200PB	TO-220AB (3)	1200
CLA30E1200PC	TO-263AB (D2Pak) (2)	1200
CLA30E1200HB	TO-247AD (3)	1200
CS22-08io1M	TO-220ABFP (3)	800



Equivalent Circuits for Simulation

* on die level


 $T_{VJ} = 150^\circ\text{C}$

	Thyristor	
$V_{0\max}$	threshold voltage	0.9 V
$R_{0\max}$	slope resistance *	14 mΩ

Outlines TO-220FP



Dim.	Millimeters		Inches	
	min	max	min	max
A	4.50	4.90	0.177	0.193
A1	2.34	2.74	0.092	0.108
A2	2.56	2.96	0.101	0.117
b	0.70	0.90	0.028	0.035
c	0.45	0.60	0.018	0.024
D	15.67	16.07	0.617	0.633
E	9.96	10.36	0.392	0.408
e	2.54 BSC		0.100 BSC	
H	6.48	6.88	0.255	0.271
L	12.68	13.28	0.499	0.523
L1	3.03	3.43	0.119	0.135
Ø P	3.08	3.28	0.121	0.129
Q	3.20	3.40	0.126	0.134



Thyristor




Fig. 1 Forward characteristics






Fig. 2 Surge overload current
 I_{TSM} : crest value, t : durationFig. 3 I^2t versus time (1-10 s)Fig. 4 Gate voltage & gate current
Triggering: A = no; B = possible; C = safeFig. 5 Gate controlled delay time t_{gd} 

Fig. 6 Max. forward current at case temperature



Fig. 7a Power dissipation versus direct output current
Fig. 7b and ambient temperature

Fig. 7 Transient thermal impedance junction to case