


CS
Split Nylon Conduit



- Temperature range: -40°F - 300°F (-40°C - 149°C)
- Split design for easy installation and removal of wiring
- Cable protection for electrical wiring harnesses
- Flexible body allows for corner/elbow wiring
- Can be used to protect hydraulic hoses



Material: UL94 HB Nylon Color: Black with Grey Stripe							
Part No	Nominal Ø	"A" Min	"A" Max	"B" Min	"B" Max	Wall Thickness	Standard Pack
CS1020A	3/8 (9.5)	.341 (8.7)	.380 (9.7)	.497 (12.6)	.526 (13.4)	.004 (.1)	1,900 Ft (579.1m)
CS1040A	7/16 (11.1)	.399 (10.1)	.437 (11.1)	.573 (14.6)	.597 (15.2)	.005 (.1)	1,500 Ft (457.2m)
CS1060A	1/2 (12.7)	.473 (12.0)	.516 (13.1)	.664 (16.9)	.700 (17.8)	.005 (.1)	1,100 Ft (335.3m)
CS1080A	5/8 (15.9)	.603 (15.3)	.639 (16.2)	.805 (20.5)	.837 (21.3)	.005 (.1)	800 Ft (243.8m)
CS1090A	3/4 (19.1)	.707 (18.0)	.759 (19.3)	.950 (24.1)	.989 (25.1)	.005 (.1)	550 Ft (164.6m)
CS1140A	1 (25.4)	1.020 (25.9)	1.069 (27.2)	1.251 (31.8)	1.304 (33.1)	.006 (.2)	300 Ft (91.4m)