



CTT60R0HIRM4

Compression Tie, 8" Long, 20lb Tensile Strength, PA66HIRHS, Black, 1000/pkg

Article Number: 112-52109

Part Number: CTT60R0HIRM4

Type: CTT60R

Base Data

Part No.	CTT60R0HIRM4
Type	CTT60R
Color	Black (BK)
Features	• High impact and heat stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Typical Application	The clamps are recommended for soft rubber hose applications including fuel, water, and air vacuum lines.
Variant	Inside Serrated

Product Dimensions

Min. Tensile Strength	60.0lbs / 265.0N
Length (L)	8.0" / 205.0mm
Width (W) (imperial)	0.19"
Width (W)	4.7mm
Min. Ø Bundle	0.06" / 1.5mm
Max. Ø Bundle	1.8" / 45.0mm

Material and Specifications

Material

	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
CSA Certified	No
Flammability	UL94 HB
Material Specification	RoHS
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	 RoHS
Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

Logistic and Packaging

Packaging Type	bag
Pkg. Qty.	1000
Carton Qty.	5000
EAN code	4031026424507
UPC	089306014454

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001 Certified](#)
 7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512