





RECOMMENDED P.C.B. LAYOUT

NOT TO SCALE



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $X.XX = \pm 0.25$
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATINGS: 12VDC, 50mA
5. CONTACT MATERIAL: SILVER
6. OPERATING FORCE: $180 \pm 50 \text{gf}$
7. TRAVEL: $0.25 \pm 0.1 \text{mm}$
8. CONTACT RESISTANCE: 100mILLI-Ohms Max.
9. MECHANICAL/ELECTRICAL LIFE: 50,000 CYCLES
10. PACKAGE: BULK
11. 2002/95/EC (ROHS) COMPLIANT



E-SWITCH®			
TITLE		TL1107BF180BQ	
SCALE		4:1	
DATE		11/9/2006	
DR		TN	
DWG		D310383	
REV		B	

B	16638	UPDATED NOTES	11/9/2006	TN
A	12384	RELEASED FOR PRODUCTION	11/21/02	CJB
REV.	ECN NO.	DESCRIPTION	DATE	CHKD
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED				