




RECOMMENDED MOUNTING PAD
SCALE: 4:1



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 50mA, @12V DC
5. BODY & STEM: PPS RYTUN R-4
6. OPERATING FORCE: 160gf +50/-30grams
7. TRAVEL: 0.25 +0.2/-0.1mm
8. CONTACT RESISTANCE: 100 ohms max.
9. PACKAGED: TAPE & REEL (QTY 700)
10. DESIGNATE MAJOR FEATURE:
11. 2002/95/EC (ROHS) COMPLIANT.
14. REEL WIDTH: 16.0mm

C	19360	UPDATE MISC. NOTES	10/18/10	BMA	 E-SWITCH [®]  LAMB [®] INDUSTRIES	TITLE	TL 3301 SP F160 Q J (TAPE & REEL)		
B	18606	CHANGE PART QUANTITY PER REEL	9/15/09	BLR					
A	11586	RELEASED FOR PRODUCTION	7/30/01	CB					
REV.	ECN No.	DESCRIPTION	DATE	CHKD					
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE	DATE	DR	DWG	REV
					3:1	9/15/09	BLR	D310674	C