









P.C.B. LAYOUT




CIRCUIT: SPST

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=± 0.4
X.XX=± 0.25
3. TERMINAL NUMBERS FOR REFERENCE ONLY.
4. RATING: 12VDC 50mA
- ▲5. OPERATING FORCES: 130± 30gf
6. TRAVEL: 0.25± 0.1 mm
7. CONTACT RESISTANCE: 100m OHMS MAX
8. INSULATION RESISTANCE: 100M OHMS MIN.
9. DIELECTRIC STRENGTH: 250VAC FOR 1 MINUTE.
10. OPERATING TEMP: -20C TO +70C
11. STORAGE TEMPERATURE: -40C TO + 80C
12. LIFE: 80,000 CYCLES.
- ▲13. PACKAGING: TAPE & REEL, 500 PIECES PER REEL.
14. ▲DENOTES CRITICAL PARAMETER.
15. 2002/95/EC (RoHS) COMPLIANT AND HALOGEN FREE



2 (①, ②) SURFACES COPLANAR
WITHIN 0.1 mm MAX.



TITLE TL3320AF130Q

SCALE 4:1

DATE 3/22/2010

DR RC

DWG D320001

REV G

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

G	19632	CHANGE ACTUATOR HEIGHT	01/31/11	BMA
REV	PCR NO	DESCRIPTION	DATE	BY