

	1	2	3	4	5	6	7	
A								A
B								B
C	Material: - Conductor: 26AWG 7*0.16±0.015mm - Conductor Insulation color coding: (1) White/Orange, (1) Orange, (1) White/Green, (1) Green, (1) Blue, (1) White/Blue, (1) White/Brown, (1) Brown - Cable jacket printing: CM (UL) C(UL) 4P 26AWG UTP CAT.5E PATCH CABLE ISO/IEC 11801 & EN 50288 & ANSI/TIA-568-C.2 - Wiring T568B Color - P1 & P2 Contact plug: RJ45 8P8C gold plating pc UL 94V-2 - Cable tie: White - Cable jacket color: Black, White, Blue, or Grey - Dielectric strength: 2.5KV dc-2seconds - Working temperatures: -20°C ~ +60°C							C
D								D
E								E
F								F
G								G
H								H
	1	2	3	4	5	6	7	

PIN OUT		
P1	WIRE COLOR	P2
1	ORANGE/WHITE	1
2	ORANGE	2
3	GREEN/WHITE	3
6	GREEN	6
4	BLUE	4
5	BLUE/WHITE	5
7	BROWN/WHITE	7
8	BROWN	8

Order Code: DK-1511-26-xxx/x
Order lengths in feet: 1,3,5,7,10,15, 20,25,50,100
Cable Jacket colors: Black(BL), White(WH), Blue(B), or Grey(G)

Scale	Free					Date	Name	Title
TOLERANCE						Drawn	23.04.13	Wilson
X.	±0.3					Approved	23.04.13	Groll
X.X	±X							
X.XX	±X							
DIM	TOL							
X.°	±X°							
X.X°	±X°	①	Drawn	23.04.13	Wilson			
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN
WSW components
1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@assmann.us

Cat5e UTP Patch cable Unshielded/Booted, 26AWG, gold plating	
ASSMANN WSW-No. DK-1511-26-xxx/x	
Drawing-No.	rev00
Replace	Sheet 1/1