



P2




P1

Material:

- 4x2, 24AWG, twisted pair, $7 \times 0.19 \pm 0.15\text{MM}$
- OD: $6.0\text{MM} \pm 0.30\text{MM}$
- Insulation: HDPE-8380
- Jacket: PVC
- Contact Plug: UTP RJ45, 50μ "
- 568B Color wire standard
- Molded snagless boot with strain relief
- Spot length on boot
- Connection: 1:1



1	2	3	4
BLU WH/BLU	ORG WH/ORG	GRN WH/GRN	BWN WH/BWN



80 cables per carton

PIN OUT

P1	568B Color	P2
1	White/Orange	1
2	Orange	2
3	White/Green	3
4	Blue	4
5	White/Blue	5
6	Green	6
7	White/Brown	7
8	Brown	8

Ⓐ = Assmann logo



ITEM NO.

DK-1611-015/WH

TITLE

CAT6 Patch Cord - Unshielded, Booted, 15 Feet,
UTP, 24AWG, Contact Plating 50μ " of Gold, White

ASSMANN

Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2010 by Assmann Electronic Components
All International Rights Reserved