

	1	2	3	4	5	6	7																																																																																										
A	P2								A																																																																																								
B									B																																																																																								
C	P1 <table border="1"> <thead> <tr> <th colspan="3">PIN OUT</th> </tr> <tr> <th>P1</th> <th>568B Color</th> <th>P2</th> </tr> </thead> <tbody> <tr><td>1</td><td>White/Orange</td><td>1</td></tr> <tr><td>2</td><td>Orange</td><td>2</td></tr> <tr><td>3</td><td>White/Green</td><td>3</td></tr> <tr><td>4</td><td>Blue</td><td>4</td></tr> <tr><td>5</td><td>White/Blue</td><td>5</td></tr> <tr><td>6</td><td>Green</td><td>6</td></tr> <tr><td>7</td><td>White/Brown</td><td>7</td></tr> <tr><td>8</td><td>Brown</td><td>8</td></tr> </tbody> </table> 25 cables per carton								PIN OUT			P1	568B Color	P2	1	White/Orange	1	2	Orange	2	3	White/Green	3	4	Blue	4	5	White/Blue	5	6	Green	6	7	White/Brown	7	8	Brown	8	C																																																										
PIN OUT																																																																																																	
P1	568B Color	P2																																																																																															
1	White/Orange	1																																																																																															
2	Orange	2																																																																																															
3	White/Green	3																																																																																															
4	Blue	4																																																																																															
5	White/Blue	5																																																																																															
6	Green	6																																																																																															
7	White/Brown	7																																																																																															
8	Brown	8																																																																																															
D	Material: • 4X2, 24AWG, twisted pair, 7*0.19±0.15MM - OD: 6.0MM±0.30MM • Insulation: HDPE-8380 • Jacket: PVC • Contact Plug: UTP RJ45, 50μ" • 568B Color wire standard • Molded snagless boot with strain relief • Spot length on boot • Connection: 1:1								D																																																																																								
E	<table border="1" style="width: 100%;"> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> </tr> <tr> <td>BLU WH/BLU</td> <td>ORG WH/ORG</td> <td>GRN WH/GRN</td> <td>BWN WH/BWN</td> </tr> </table>								1	2	3	4	BLU WH/BLU	ORG WH/ORG	GRN WH/GRN	BWN WH/BWN	E																																																																																
1	2	3	4																																																																																														
BLU WH/BLU	ORG WH/ORG	GRN WH/GRN	BWN WH/BWN																																																																																														
F	<table border="1" style="width: 100%;"> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> </tr> <tr> <td>BLU WH/BLU</td> <td>ORG WH/ORG</td> <td>GRN WH/GRN</td> <td>BWN WH/BWN</td> </tr> </table>								1	2	3	4	BLU WH/BLU	ORG WH/ORG	GRN WH/GRN	BWN WH/BWN	F																																																																																
1	2	3	4																																																																																														
BLU WH/BLU	ORG WH/ORG	GRN WH/GRN	BWN WH/BWN																																																																																														
G	Unit: mm RoHS Compliant <table border="1"> <tr> <td>Scale</td> <td>Free</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2">TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.</td> <td>±0.3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> <td></td> </tr> </table> ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us <table border="1"> <tr> <td>Date</td> <td>Name</td> <td rowspan="3"> Cat6 UTP Patch cable Unshielded, Booted, White, 50ft </td> </tr> <tr> <td>Drawn</td> <td>Chappell</td> </tr> <tr> <td>Approved</td> <td></td> </tr> </table>								Scale	Free								TOLERANCE									X.	±0.3								X.X	±X								X.XX	±X								DIM	TOL								X.°	±X°								X.X°	±X°								Angle	TOL	Id.	Modification	Date	Name				Date	Name	Cat6 UTP Patch cable Unshielded, Booted, White, 50ft	Drawn	Chappell	Approved		G
Scale	Free																																																																																																
TOLERANCE																																																																																																	
X.	±0.3																																																																																																
X.X	±X																																																																																																
X.XX	±X																																																																																																
DIM	TOL																																																																																																
X.°	±X°																																																																																																
X.X°	±X°																																																																																																
Angle	TOL	Id.	Modification	Date	Name																																																																																												
Date	Name	Cat6 UTP Patch cable Unshielded, Booted, White, 50ft																																																																																															
Drawn	Chappell																																																																																																
Approved																																																																																																	
H	<table border="1"> <tr> <td colspan="2">ASSMANN WSW-No.</td> </tr> <tr> <td colspan="2" style="text-align: center;">DK-1611-050/WH</td> </tr> <tr> <td>Drawing-No.</td> <td>rev00</td> </tr> </table> <table border="1"> <tr> <td>Replace</td> <td>Sheet 1/1</td> </tr> </table>								ASSMANN WSW-No.		DK-1611-050/WH		Drawing-No.	rev00	Replace	Sheet 1/1	H																																																																																
ASSMANN WSW-No.																																																																																																	
DK-1611-050/WH																																																																																																	
Drawing-No.	rev00																																																																																																
Replace	Sheet 1/1																																																																																																
	1	2	3	4	5	6	7																																																																																										