

Part Number: E3522S

Revision: 9/6/2013

2C 14 AWG PVC, UNSH, PVC**FIRE ALARM****A. CONSTRUCTION**

Conductor: #14 AWG (solid) Bare Copper

Insulation: .010" Wall, Plenum PVC

Cable Assembly: 2C with an 8.00" LHL

Ripcord: Plenum Ripcord

Jacket: .015" Wall, Plenum PVC

Print Legend: **CAROL (R) 14 AWG -- E3522S -- 75C TYPE FPLP E66267-8 (UL) -- ROHS -- MADE IN USA**
(date code - MM/YY) (sequential footage)**DIAMETERS**

.064" Nom

.084" Nom

.168" Nom

.198" ± .010"

B. INDUSTRY APPROVALS

National Electrical Code

Article 760

UL Standard 1424

Type FPLP

C. ELECTRICAL PROPERTIES

Temperature:

0° to +75°C

Suggested Working Voltage:

300 Vrms (Max)

Conductor DCR:

2.57 Ohms/1000ft @ 20°C (Max)

Capacitance (Cond-Cond):

36.7 pF/ft. @ 1 kHz (Nom)

D. COLOR CODE

COND	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____

Date: _____