

HRS DRAFTING FOR EXPORT

SIGNAL PORTION CROSS SECTION (10 : 1)

GROUND PORTION CROSS SECTION (10 : 1)

RECOMMENDED LAND PATTERN DIMENSION OF PCB

NOTES

- 12 HATCHED PARTS: GROUND CIRCUIT.
- SMT LEAD-COPLANARITY: 0.1 MAX.
- THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
- MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND, OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED AREA.)
- DO NOT MOUNT OTHER DEVICES ONTO AREA, OR MATING PAIR CANNOT BE MATED.
- TO BE EMBOSSED CARRIER TAPED AS SPECIFIED IN SHEET 2.
- THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
1	LCP	BEIGE	UL94V-0	4	PHOSPHOR BRONZE	TIN PLATING	
				3	PHOSPHOR BRONZE	TIN PLATING	
				2	COPPER ALLOY		CONTACT AREA : GOLD 0.1μm min. LEAD AREA : GOLD FLASH UNDER PLATING : NICKEL 1μm min.

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1					

APPROVED : HS. OKAWA 07.07.26
CHECKED : HS. OZAWA 07.07.26
DESIGNED : SY. KAMIGA 07.07.26
DRAWN : HK. SUNADORI 07.07.24

DRAWING NO. EDC3-152099-21
PART NO. FX11LB-120P/12-SV(91)
CODE NO. CL573-0015-9-91

HRS HIROSE ELECTRIC CO., LTD.

DRAWING F
08/11/2012

