



TO



NOTE 1 LEAD-COPLANARITY OF THIS PRODUCT TO BE 0.1MAX FOR SMT LEAD AND 0.15MAX FOR GROUND PLATE LEAD.
 2  AREA, OR MATINGPAIR CANNOT BE MATED AND OPERATED THE LOCK PARTS.
 3  AREA OF INNER SMT LAND REQUIRES PATTERN PROHIBITION OR RESIST TREATMENT TO PREVENT THE PATTERN TOUCHING TO THE CONTACTS.
 4  AREA IS VACUUM PICKUP AREA FOR REFERENCE.
 5 THE DIMENSION IS THE CENTER OF VACUUM PICKUP AREA.
 6 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
 7 PACKAGING FOR THIS PRODUCT APPLIES EMBOSSED CARRIER TAPE PACKAGING.
 SEE SHEET 2/2 FOR DETAILS.

3	NICKEL SILVER		2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min		
1	PA	BLACK UL94V-0			LEAD AREA:TIN-PLATING 1μm min		
NO.	MATERIAL	FINISH, REMARKS			UNDER PLATING:NICKEL 0.5μm min		
NO.			MATERIAL		FINISH, REMARKS		
CODE NO. (OLD) CL			DRAWN K. SHIBUYA 05.08.04	DESIGNED K. Shibuya 05.08.04	CHECKED H. Yamaguchi 05.08.05	APPROVED H. Kanwa 05.08.05	RELEASED .
DRAWING NO. EDC3-155937			PART NO. FX15S-41S-0.5SH				
 SCALE 4 : 1 UNITS mm			 HIROSE ELECTRIC CO., LTD				CODE NO. CL575-2307-8
							1/2

TO

