

Part Number EEG · 1K · 308 ·

EEG.1K.308.CLL

Size/Series 1K / K

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model EE*: Fixed receptacle, nut fixing (back panel mounting)
Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing : 0 - 0 mm
Variant :


	A	B	E	L	M	N	P	S1	e
mm.	20	20	6.2	27	3.5	25.1	10	14.5	M16x1.0
in.	0.79	0.79	0.24	1.06	0.14	0.99	0.39	0.57	

PERFORMANCE DETAILS

Insert Configuration 1K.308 : 8 Low Voltage
Insulator L: PEEK
Specifications
Contact Type: Solder
Max. Matings: 5000
Contact Dia.: 0.7 mm (0.028in)
Bucket Dia.: 0.8 mm (0.031in)
Max. Solid Conductor: 0.34 mm² (AWG 22)
Max. Stranded Conductor: 0.34 mm² (AWG 22)
R (max): 6.1 mOhm
Vtest (contact-shell): 1150 V (AC), 1630 V (DC)
Vtest (contact-contact): 950 V (AC), 1340 V (DC)
Rated Current: 5 A (AC/DC)

OTHER CHARACTERISTICS

Humidity (max): <=95% [at 60 deg C /140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [6 ms]
Salt Spray Corrosion: >144 hr
Climatical Category: 50/175/21
Shielding (min): 95 dB (10 MHz)
Shielding (min): 80 dB (1 GHz)
IP Rating 68
Catalog

[Download 3D draw](#)[Copyright](#) [Privacy policy](#) [Product safety](#)

