

Part Number **EGN.2M.319.XLM**

Size/Series 2MN / M

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model	EG*: Fixed receptacle, nut fixing
Keying	3 keys (beta=165, gamma=30, plug: male contacts, receptacle: female contacts)
Housing Material	Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass
Cable Fixing	J : 0 - 0 mm
Variant	:



	C	D	E	L	P	S1	S2	e
mm.	17.2	6.8	4.5	18.1	5.3	12.5	17.0	M14x1.0
in.	0.68	0.27	0.18	0.71	0.21	0.49	0.67	

PERFORMANCE DETAILS

Insert Configuration	2M.319 : 19 Low Voltage
Specifications	
Contact Type:	Crimp
Max. Matings:	5000
Contact Retention:	22 N
Contact Dia.:	0.7 mm (0.028in)
Bucket Dia.:	0.8 mm (0.031in)
Min. Conductor:	0.14 mm ² (AWG 26)
Max. Conductor:	0.34 mm ² (AWG 22)
R (max):	6.1 mOhm
Test voltage (kV rms)	1.55
Contact-contact:	
Test voltage (kV rms)	0.95
Contact-shell:	
Rated current (A):	5

OTHER CHARACTERISTICS

Humidity (max):	<=95% [at 60 deg C /140 F]
Vibration:	15 g [10 Hz - 2000 Hz]
Shock Resistance:	100 g [6 ms]
Operating temperature:	-55°C/ +200°C
Climatical Category:	15/200/21 (Al. shell)
Lighting strike EIA 364-75	10K amps - 6 times
EMI Shielding EIA 364-66A	- 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB
IP Rating	68
Catalog	

[Copyright](#) [Privacy policy](#) [Product safety](#)