


COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICATION STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C	STORAGE TEMPERATURE RANGE		
	VOLTAGE	AC 50 V	OPERATING HUMIDITY RANGE		
	CURRENT	0.3 A	RELATIVE HUMIDITY: 95 % MAX (NO DEW CONDENSATION IS PERMITTED)		
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENT	QT/AT		
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING	X X		
MARKING	CONFIRMED VISUALLY.		X X		
ELECTRICAL CHARACTERISTICS					
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	70 mΩ MAX.	X X		
INSULATION RESISTANCE	100 V DC	100 MΩ MIN.	X -		
VOLTAGE PROOF	150 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X X		
MECHANICAL CHARACTERISTICS					
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR	INSERTION FORCE: 60 N MAX WITHDRAWAL FORCE: 2.5 N MIN.	X -		
MECHANICAL OPERATION	50 TIMES INSERTION AND EXTRACTIONS.	1) CONTACT RESISTANCE: 80 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X -		
VIBRATION	FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE: 0.75 mm, → m/s ² AT 10 CYCLES FOR 3 DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 1 μs MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X -		
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X -		
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90~95 %, 96 h.	1) CONTACT RESISTANCE: 80 mΩ MAX. 2) INSULATION RESISTANCE: 100 MΩ MIN.	X -		
RAPID CHAGE OF TEMPERTURE	TEMPERTURE -55→15~35→ 85→15~35°C TIME 30→ 2~ 3→ 30→ 2~ 3 min. UNDER 5 CYCLES.	3) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X -		
DRY HEAT	EXPOSED AT 85 °C, 96 h.	1) CONTACT RESISTANCE: 80 mΩ MAX.	X -		
COLD	EXPOSED AT -55 °C, 96 h.	2) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X -		
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	X -		
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JIS C 0090)	1) CONTACT RESISTANCE: 80 mΩ MAX. 2) NO HEAVY CORROSION.	X -		
RESISTANCE TO SOLDERING HEAT	REFLOW, RECOMMENDED TEMPERATURE PROFILE  TO BE TESTED UNDER THE ABOVE CONDITIONS.	NO MELTING OF RESIN WHICH AFFECTS THE PERFORMANCE OF COMPONENT	X -		
SOLDRABILITY	SOLDERED AT SOLDER TEMPERATURE, 235 °C FOR IMMERSION DURATION, 2 s	NO PINHOLE OR DEWETTING ON SOLDERED SURFACE.	X -		
REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	<i>J. Matsukawa</i>	<i>J. Matsukawa</i>	<i>M. Ishida</i>	<i>T. Fujimori</i>	
UNLESS OTERWISE SPECIFIED, REFER TO JIS C 5402.	00.01.15	00.01.15	00.01.17	00.01.17	
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST					
HRS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO.	
CODE NO.(OLD)		DRAWING NO.		CODE NO.	
CL		ELC4 - 152606 - 01		CL 573 - 0543 - 7 - 21	
				1/1	

DRAWING FOR REFERENCE: This is subject to change without notice
08/11/2012

TO
PCK