




APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾	
	VOLTAGE	100 V AC ⁽³⁾	OPERATING HUMIDITY RANGE	40 % TO 80 %	
	CURRENT	0.5 A ⁽³⁾	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾	
	APPLICABLE CABLE	AWG 36,40 THIN COAXIAL CABLE			
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING		CONFIRMED VISUALLY.		×	×
<div style="position: absolute; top: 50%; left: 50%; transform: translate(-50%, -50%) rotate(-45deg); opacity: 0.1; font-size: 100px; pointer-events: none;"> DRAWING FOR REFERENCE </div>					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
					
REMARKS ⁽¹⁾ INCLUDE TEMPRERATURE RISE CAUSED BY CURRENT-CARRYING. ⁽²⁾ “STORAGE” MEANS A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE ASSEMBLY TO PCB. ⁽³⁾ IT IS THE MAXIMUM VALUE OF CONNECTOR. CONFIRM THE SPECIFICATION OF THE CABLE. Unless otherwise specified, refer to JIS-C-5402.			APPROVED	HS. OKAWA	07. 05. 11
			CHECKED	HT. YAMAGUCHI	07. 05. 11
			DESIGNED	KN. SHIBUYA	07. 05. 10
			DRAWN	KN. SHIBUYA	07. 05. 10
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-156255-00
	SPECIFICATION SHEET		PART NO.	FX15S-41P-GND	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL575-2111-6-00	 1/1