






EM-27692-C14

SHT 1.1

NOTE:

1. INCREASED PRESSURE AT SOUND INLET
CAUSES A POSITIVE GOING VOLTAGE TO
APPEAR AT THE OUTPUT TERMINAL,
RELATIVE TO THE NEGATIVE TERMINAL.



NOMINAL WEIGHT
.08 GRAMS

DIMENSIONS IN MILLIMETERS [INCHES]

Revision	C.O. #	Implementation Date	RELEASE LEVEL	REVISION
F	MI0104543	3-13-12	Active	F
E	MI0104420	1-12-12		
D	MI0103578	3-26-10		

SCALE: 4:1

DO NOT SCALE DRAWING

TITLE: MICROPHONE


OUTLINE DRAWING

EM-27692-C14

SHT 1.1

DR. BY	DATE
MMM	12-22-05
CK. BY	DATE
GJP	1-2-06
APP. BY	DATE
GJP	1-2-06

KNOWLES ELECTRONICS
ITASCA, ILLINOIS U.S.A.



FREQUENCY	SENSITIVITY			DEVICE CONFORMITY	
	MIN.	NOM.	MAX.	RANGE OF DEVIATION FROM 1KHz	
100	---	-59.5	---	-3.5	-0.0
1000	-60.5	-57.5	-54.5	0.0	0.0
≈ 4000	---	-56.5	---	-2.0	+4.0

NOTES:

- CASE CONNECTED TO NEGATIVE TERMINAL.
- MICROPHONE TO BE FUNCTIONAL WITH 1.6 VDC SUPPLY.
- TYPICAL SENSITIVITY TO HUMIDITY AT 1000Hz IS 0.06 dB/%RH
- SENSITIVITY AND NOISE VALUES INDICATED ON THIS SPECIFICATION ARE VALID AT 50% HUMIDITY.

PORT LOCATION	DC SUPPLY	AMPLIFIER CURRENT DRAIN	SENSITIVITY CHANGE ON REDUCING SUPPLY TO 0.9VDC	"A" WEIGHTED NOISE (1 KHz EQUIV. SPL)	OUTPUT IMPEDANCE OHMS		
					MIN.	NOM.	MAX.
12KP	1.3V	50 μA MAX.	3 dB MAX.	28.0 dB MAX.	2800	4400	6800

KNOWLES ELECTRONICS
ITASCA, ILLINOIS U.S.A.

Revision	C.O. #	Implementation Date	RELEASE LEVEL		REVISION
F	M10104543	3-13-12	Active		F
E	M10104420	1-12-12			
D	M10103578	3-26-10			
WHEN TEST LIMITS ARE USED TO ESTABLISH INCOMING INSPECTION ACCEPTANCE/REJECTION CRITERIA, CORRELATION OF TEST EQUIPMENT WITH KNOWLES IS ALSO REQUIRED FOR ELIMINATION OF EQUIPMENT AND TEST METHOD VARIATION			DR. BY	DATE	
			MMM	12-22-05	
TITLE: MICROPHONE PERFORMANCE SPECIFICATION			CK. BY	DATE	
			GJP	1-2-06	
EM-27692-C14 SHT 2.1			APP. BY	DATE	
			GJP	1-2-06	