

NW7 SERIES

Bi-polar, 7mm Height

◆FEATURES

•RoHS compliance.

**◆SPECIFICATIONS**

Items	Characteristics																											
Category Temperature Range	−40~+85°C																											
Rated Voltage Range	6.3~50V.DC																											
Capacitance Tolerance	±20% (20°C, 120Hz)																											
Leakage Current(MAX)	I=0.05CV or 10μA whichever is greater. (After 5 minutes application of rated voltage) I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(V)																											
Dissipation Factor(MAX) (tanδ)	<table border="1"> <tr> <th>Rated Voltage (V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> <tr> <th>tanδ</th> <td>0.26</td> <td>0.22</td> <td>0.18</td> <td>0.17</td> <td>0.15</td> <td>0.14</td> </tr> </table> (20°C, 120Hz)							Rated Voltage (V)	6.3	10	16	25	35	50	tanδ	0.26	0.22	0.18	0.17	0.15	0.14							
Rated Voltage (V)	6.3	10	16	25	35	50																						
tanδ	0.26	0.22	0.18	0.17	0.15	0.14																						
Endurance	After applying rated voltage with rated ripple current for 1000hrs at 85°C, (The polarity shall be reversed every 500hrs.), the capacitors shall meet the following requirements. <table border="1"> <tr> <td>Capacitance Change</td> <td>Within ±25% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>							Capacitance Change	Within ±25% of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.															
Capacitance Change	Within ±25% of the initial value.																											
Dissipation Factor	Not more than 200% of the specified value.																											
Leakage Current	Not more than the specified value.																											
Low Temperature Stability Impedance Ratio(MAX)	<table border="1"> <tr> <th>Rated Voltage (V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> <tr> <td>Z(−25°C)/Z(20°C)</td> <td>4</td> <td>3</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z(−40°C)/Z(20°C)</td> <td>10</td> <td>8</td> <td>6</td> <td>4</td> <td>4</td> <td>4</td> </tr> </table> (120Hz)							Rated Voltage (V)	6.3	10	16	25	35	50	Z(−25°C)/Z(20°C)	4	3	3	2	2	2	Z(−40°C)/Z(20°C)	10	8	6	4	4	4
Rated Voltage (V)	6.3	10	16	25	35	50																						
Z(−25°C)/Z(20°C)	4	3	3	2	2	2																						
Z(−40°C)/Z(20°C)	10	8	6	4	4	4																						

◆DIMENSIONS

(mm)																											
<table border="1"> <tr> <td>φD</td> <td>4</td> <td>5</td> <td>6.3</td> <td></td> <td></td> <td></td> </tr> <tr> <td>φd</td> <td colspan="3">0.45</td><td></td><td></td><td></td> </tr> <tr> <td>F</td> <td>1.5</td> <td>2.0</td> <td>2.5</td> <td></td><td></td><td></td> </tr> </table>							φD	4	5	6.3				φd	0.45						F	1.5	2.0	2.5			
φD	4	5	6.3																								
φd	0.45																										
F	1.5	2.0	2.5																								

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

	Frequency(Hz)	60(50)	120	500	1k	10k≤
Coefficient	0.33~1μF	0.50	1.00	1.20	1.30	1.50
	2.2~4.7μF	0.65	1.00	1.20	1.30	1.50
	10~47μF	0.80	1.00	1.20	1.30	1.50

◆OPTION

	Code
PET Sleeve	EFC

◆STANDARD SIZE

WV (V.DC)	Cap (μF)	Size (φDxL)	Rated Ripple Current
6.3 (0J)	22	5×7	32
	33	5×7	40
	47	6.3×7	56
10 (1A)	10	4×7	23
	22	5×7	35
	33	6.3×7	45
	47	6.3×7	65
	3.3	4×7	15

WV (V.DC)	Cap (μF)	Size (φDxL)	Rated Ripple Current
16 (1C)	4.7	4×7	18
	10	4×7	25
	22	6.3×7	45
	33	6.3×7	60
	47	6.3×7	65
25 (1E)	3.3	4×7	15
	4.7	4×7	18
	10	6.3×7	35
	22	6.3×7	50

WV (V.DC)	Cap (μF)	Size (φDxL)	Rated Ripple Current
35 (1V)	2.2	4×7	13
	3.3	5×7	19
	4.7	5×7	22
	10	6.3×7	37
	0.33	4×7	3
50 (1H)	0.47	4×7	5
	1	4×7	10
	2.2	5×7	15
	3.3	5×7	19
	4.7	6.3×7	26

◆PART NUMBER

□□□ NW7 □□□□ M □□□ Option □□ Lead Forming □□ Case Size

Rated Voltage NW7 Series Capacitance Tolerance Option Lead Forming Case Size