

YXM SERIES

Load Life : 105°C 10000 hours, Miniaturized.

◆FEATURES


- Miniaturized Long Life.
- RoHS compliance.

◆SPECIFICATIONS

Items	Characteristics																							
Category Temperature Range	-25~+105℃																							
Rated Voltage Range	10~100V.DC																							
Capacitance Tolerance	±20% (20℃,120Hz)																							
Leakage Current(MAX)	I=0.01CV or 3μA whichever is greater.(After 2 minutes) I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(V)																							
Dissipation Factor(MAX) (tanδ)	<table><tr><td>Rated Voltage (V)</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>100</td></tr><tr><td>tanδ</td><td>0.45</td><td>0.35</td><td>0.30</td><td>0.22</td><td>0.19</td><td>0.17</td><td>0.15</td></tr></table> (20℃,120Hz)								Rated Voltage (V)	10	16	25	35	50	63	100	tanδ	0.45	0.35	0.30	0.22	0.19	0.17	0.15
Rated Voltage (V)	10	16	25	35	50	63	100																	
tanδ	0.45	0.35	0.30	0.22	0.19	0.17	0.15																	
Endurance	After applying rated voltage with rated ripple current for 10000 hours at 105℃, the capacitors shall meet the following requirements.																							
	Capacitance Change			Within ±25% of the initial value.																				
	Dissipation Factor			Not more than 300% of the specified value.																				
Low Temperature Stability Impedance Ratio(MAX)	Leakage Current			Not more than the specified value.																				
	<table><tr><td>Rated Voltage (V)</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>100</td></tr><tr><td>Z(-25℃)/Z(20℃)</td><td>8</td><td>6</td><td>4</td><td>4</td><td>3</td><td>3</td><td>3</td></tr></table> (120Hz)								Rated Voltage (V)	10	16	25	35	50	63	100	Z(-25℃)/Z(20℃)	8	6	4	4	3	3	3
	Rated Voltage (V)	10	16	25	35	50	63	100																
Z(-25℃)/Z(20℃)	8	6	4	4	3	3	3																	

◆DIMENSIONS

(mm)



◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)	120	1k	10k	100k≤
Coefficient				
1~10μF	0.42	0.60	0.80	1.00
22~33μF	0.55	0.75	0.90	1.00
47~330μF	0.70	0.85	0.95	1.00

◆STANDARD SIZE

Size φD×L(mm), Ripple Current (mA r.m.s./105°C, 100kHz)

V.DC	Cap (μF)	Size	Rated Ripple Current
10 (1A)	100	5×11	130
	220	6.3×11	210
	330	8×11.5	330
16 (1C)	47	5×11	130
	100	6.3×11	210
	220	8×11.5	330
25 (1E)	33	5×11	130
	47	5×11	130
	100	6.3×11	210

V.DC	Cap (μF)	Size	Rated Ripple Current
35 (1V)	33	5×11	130
	47	6.3×11	210
	100	8×11.5	330
50 (1H)	1	5×11	25
	2.2	5×11	35
	3.3	5×11	70
	4.7	5×11	80
	10	5×11	90
	22	5×11	135
	33	6.3×11	190
	47	6.3×11	190
	100	8×11.5	270

V.DC	Cap (μF)	Size	Rated Ripple Current
63 (1J)	10	5×11	80
	22	6.3×11	170
	33	6.3×11	170
	47	8×11.5	240
100 (2A)	1	5×11	40
	2.2	5×11	50
	3.3	5×11	60
	4.7	5×11	70
	10	6.3×11	150
	22	8×11.5	230

◆OPTION

	Code
PET Sleeve	EFC

◆PART NUMBER

□□□	YXM	□□□□□	M	□□□	□□	D×L
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size