

Part Number 

FFA.00.250.NTAC29

Status NRND
Alternative FFA.00.250.NTAC31

Size/Series 00 / 00


Matching ERA.00.250.NTL

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model FFA*: Straight plug with cable collet
Keying Circular (can rotate)
Housing Material Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces
Cable Fixing C29: 2.8 - 3.1 mm **NEW COLLET**
Variant :

	A	L	M
mm.	6.4	26	18
in.	0.25	1.02	0.71



PERFORMANCE DETAILS

Insert Configuration 0.25 : 1 Coax (50 Ohm)
Insulator T: PTFE
Specifications
Contact Type: Coaxial 50 Ohm (Solder)
Max. Matings: 5000
Contact Dia.: 0.7 mm (0.028in)
Bucket Dia.: 0.6 mm (0.024in)
R (max): 6.1 mOhm
Vtest: 2100 V (AC), 3000 V (DC)
Rated Current: 4 A (AC/DC)
Impedance: 50 Ohm
VSWR: 1.09 + 0.11 * f/GHz
Cable type: RG 316 /U

OTHER CHARACTERISTICS

Endurance (Shell) 5000 mating cycles
F ret (min): 100 N
IP Rating 50
Catalog



 [Download 3D draw](#)

" "; "; "; "; Note: You can still get the CAD file even if no 3D preview is displayed below.

The 3D viewer requires the Java Runtime Environment (JRE) and for Java to be enabled on your system.

If Java is not installed, go to <http://www.java.com/en/download/manual.jsp>
For the Firefox users, Java can be blocked by your browser. More info on : <https://addons.mozilla.org/en-US/firefox/blocked/p80>